



φ23 2.0/25mm C	
FOCAL LENGTH	f=25mm
MAX. DIAMETER (RATIO)	F=1:2.0~16
ELEMENT	6 GROUPS 8 ELEMENTS
PICTURE SIZE	13.8x18.4mm
ANGLE	VER. ANGLE 31.1°
	HOR. ANGLE 40.9°
	DIA. ANGLE 50.2°
DISTORTION (TV)	-0.57%
SHOOTING RANGE AT	VER. 93mm
MINIMUM FOCUS	HOR. 125mm
DISTANCE	DIA. 157mm
MINIMUM FOCUS DISTANCE	0.15m
FLANGE BACK	17.526mm in air
BACK FOCUS	24.3mm in air
FILTER SCREW SIZE	M4.0x0.5
FRONT/REAR EFFECTIVE DIA.	FRONT φ31.4mm REAR φ18.2mm
MOUNT	C-MOUNT
EXIT PUPIL	-63.9mm
TEMPERATURE RANGE	-10~+50°C
STORAGE TEMPERATURE RANGE	-20~+60°C
RESOLUTION CENTER/CORNER	CENTER 160本/mm CORNER 80本/mm
LENS COATING	WIDE BAND MULTI COATING
WEIGHT	tbd g

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。

		尺度	1/1	承認	八木	製	富永
		機種名	4/3(φ23) F2.0 f=25mm				
		機種番	LM25XC				
2012.10.17	作成年月日						

For design help, accessories or pricing, please contact:
 sales@avsupply or call: 1-858-565-1101

AUDIOVIDEO SUPPLY
 1-800-284-2288 sales@avsupply.com
 www.avsupply.com

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com