



Φ23 2.0/35mm C	
FOCAL LENGTH	f=35mm
MAX. DIAMETER (RATIO)	F=1:2.0~16
ELEMENT	6 GROUPS 8 ELEMENTS
PICTURE SIZE	13.8x18.4mm
ANGLE	VER. ANGLE 22.4°
	HOR. ANGLE 29.6°
	DIA. ANGLE 36.6°
DISTORTION (TV)	-0.17%
SHOOTING RANGE AT	VER. 75mm
MINIMUM FOCUS	HOR. 100mm
DISTANCE	DIA. 125mm
MINIMUM FOCUS DISTANCE	0.2m
FLANGE BACK	17.526mm in air
BACK FOCUS	15.2mm in air
FILTER SCREW SIZE	M37.5x0.5
FRONT/REAR EFFECTIVE DIA.	FRONT Φ26.5mm REAR Φ16.9mm
MOUNT	C-MOUNT
EXIT PUPIL	-26.6mm
TEMPERATURE RANGE	-10~+50°C
STORAGE TEMPERATURE RANGE	-20~+60°C
RESOLUTION CENTER/CORNER	CENTER 160本/mm CORNER 80本/mm
LENS COATING	WIDE BAND MULTI COATING
WEIGHT	tbd g

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。

		尺度 1/1	承認 八木	製 富永 図
		機種名 4/3(Φ23) F2.0 f=35mm		
		機種番 LM35XC		
2012.10.17	作成年月日			

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

For design help, accessories or pricing, please contact:
 sales@avsupply or call: 1-858-565-1101

AUDIOVIDEO SUPPLY
 1-800-284-2288 sales@avsupply.com
 www.avsupply.com