



401DN

Composite Video to s-Video Format Converter



The **401DN** is a high-performance format converter for composite video signals. It converts a composite video input to an s-Video (Y/C) output.

FEATURES

- Bandwidth (Y) - 3.5MHz (-3dB).
- Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



401DN

TECHNICAL SPECIFICATIONS

INPUT:	1 composite video, 1Vpp/75Ω on a BNC connector.
OUTPUT:	1 s-Video, 1Vpp/75Ω (Y), 0.3Vpp/75Ω (C) on a 4-pin connector.
VIDEO BANDWIDTH (PAL):	3.5MHz.
DIFF. GAIN:	0.8%.
DIFF. PHASE:	0.4Deg.
MAX. VIDEO OUTPUT:	1.5Vpp/75Ω (Y).
LUMA S/N RATIO:	77dB.
POWER CONSUMPTION:	12V DC, 90mA.
DIMENSIONS:	12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98") W, D, H.
WEIGHT:	0.3kg (0.66lbs) approx.
INCLUDED ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.

