



6502

4x1:2 S/PDIF Switcher



The **6502** is a high-performance switcher for S/PDIF digital audio signals. The unit takes any one of four inputs, provides reclocking and equalization and distributes the signal to two identical outputs.

FEATURES

- Sampling Rates - 32kHz to 192kHz.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.
- Control - Front panel, RS-232 & IR.
- Compact Kramer TOOLST™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



6502

TECHNICAL SPECIFICATIONS

- INPUTS: 4 S/PDIF on RCA connectors.
OUTPUTS: 2 S/PDIF on RCA connectors.
SAMPLING RATE: 32kHz to 192kHz.
STANDARDS: CP1201, IEC 60958, AES3ID and S/PDIF.
DIMENSIONS: 12cm x 6.95cm x 2.44cm (4.72" x 2.74" x 0.96") W, D, H.
POWER CONSUMPTION: 5V DC, 140mA.
WEIGHT: 0.3kg (0.66lbs) approx.
INCLUDED ACCESSORIES: Power supply, mounting bracket, IR remote control transmitter.
OPTIONS: RK-3T 19" rack adapter.

