



## 908

### Stereo Audio Amplifier & Switcher (40 Watts per Channel)

---



The **908** is a high-performance audio amplifier for line-level stereo audio signals. It accepts either a balanced or an unbalanced stereo audio signal and delivers a speaker output of 40 watts RMS per channel into 8Ω loads.

### FEATURES

---

- **High Efficiency** - Class D operation.
- **Controls** - Control knob to adjust volume, bass, middle, treble and balance. Mute and loudness buttons, plus a 10V control port for adjusting the audio gain.
- **USB Port** - For firmware update.
- **Flexible Control Options** - Front panel, RS-232 (K-Router™ Windows®-based software is included), Ethernet, IR remote (included) and 10KΩ volume level.
- **Compact MegaTOOLS®** - 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-T2B universal rack adapter.



TECHNICAL SPECIFICATIONS

INPUTS: 1 unbalanced stereo audio on RCA connectors; 1 balanced stereo audio on a 5-pin terminal block connector; 1 USB connector.

OUTPUT: 1 speaker stereo audio on a 4-pin terminal block connector.

INPUT SENSITIVITY: Unbalanced: 360mVpp; balanced: 220mVpp.

MAX. VOLTAGE: Unbalanced: 35dB; balanced: 40.5dB.

GAIN:

OUTPUT POWER: 40W per channel into 8Ω.

BANDWIDTH (-3dB): 22kHz.

CROSSTALK: <-57dB @20kHz.

CONTROLS: Level: <-30dB to 35.5dB; balance: -30dB to 0dB; loudness: -14dB to 0dB @1kHz; bass: -15dB to 12dB @100Hz; mid: -15dB to 11dB @1kHz; treble: -14dB to 13dB @10kHz; input selector buttons, mute button, loudness, bass, mid, treble, balance, volume buttons, IR, RS-232, Ethernet, 10V volume control, 1 USB port for upgrading firmware.

COUPLING: Input: AC, output: DC.

AUDIO THD + NOISE: 0.15%.

AUDIO 2nd HARMONIC: 0.06%.

SIGNAL/NOISE RATIO: 63dB, 80dB @10% distortion.

AMPLIFIER TYPE: Class D.

POWER CONSUMPTION: 24V DC, 2A.

DIMENSIONS: 18.8cm x 11.4cm x 2.4cm (7.4" x 4.5" x 0.94") W, D, H.

WEIGHT: 0.6kg (1.32lbs).

INCLUDED ACCESSORIES: Power supply, Windows®-based Kramer control software, IR remote control transmitter.

OPTIONS: RK-T2B 19" rack adapter.

