



FC-322

2x1:2 3G HD-SDI to HDMI Format Converter



The FC-322 is a high-performance format converter for 3G HD-SDI signals. It converts one of two 3G HD-SDI signals to two HDMI output signals with the same resolution and frame rate.

FEATURES

- HDTV Compatible.
- Audio Group De-embedded Selection.
- Multi-Standard Operation - SDI (SMPTE 259M and SMPTE 344M), HD-SDI (SMPTE 292M) and 3G HD-SDI (SMPTE 424M).
- Active Input & Output LED Indicators.
- Switching - Front panel and IR remote (included).
- Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



FC-322

TECHNICAL SPECIFICATIONS

INPUTS: 2 SD/HD/3G HD-SDI on BNC connectors.
OUTPUTS: 2 HDMI connectors.
MAX. DATA RATE: Up to 3Gbps.
STANDARD COMPLIANCE: HDMI.
INDICATOR LEDS: SD/HD, OUT, ON.
POWER CONSUMPTION: 5V DC, 580mA.
DIMENSIONS: 12cm x 7.2cm x 2.4cm (4.7" x 2.8" x 1.0") W, D, H.
WEIGHT: 0.3kg (0.7lbs).
INCLUDED ACCESSORIES: Power supply.
OPTIONS: RK-3T 19" rack adapter.

