

PIP-4

4 Composite Video Picture-in-Picture Inserter















The PIP-4 is a high-performance picture-in-picture inserter for composite video signals. The PIP output can display up to four images simultaneously, each of which can be sized and positioned individually.

FEATURES

- Picture-In-Picture Options All inputs can be displayed simultaneously with variable window sizing and positioning and freeze frame capability. Quad button displays 4 equal-sized images.
- Multi-Format Operation s-Video and composite video outputs.
- Multi-Standard Operation PAL & NTSC compatible inputs & outputs (no format conversion).
- USB Mouse Connector For convenient navigation and control, including the OSD.
- Built-In ProcAmp Brightness, contrast, and saturation for each input.
- Flexible Control Options Front panel, IR remote, mouse (with OSD), RS-232 & Ethernet.
- Desktop Size Compact size. Two units can be rack mounted side-by-side in a 1U rack space with the optional RK-1 adapter.

PIP-4

TECHNICAL SPECIFICATIONS

INPUTS: 4 composite video, $1Vpp/75\Omega$ on BNC connectors.

OUTPUTS: 1 s-Video, 1Vpp, 0.3Vpp/75 Ω on a 4-pin connector; 1 composite video, 1Vpp/75 Ω on a BNC

connector.

DIGITAL RESOLUTION: 10 bit.

VIDEO BANDWIDTH: 5.4MHz.

K-FACTOR: 0.9%.

S/N RATIO: 64dB.

DIFFERENTIAL PHASE: 0.8Deg.

DIFFERENTIAL GAIN: 1.1%.

LUMA NON-LINEARITY: 0.9%.

CHROMA / LUMA <15ns.

DELAY:

Y/C SEPARATION: Adaptive 4-line digital comb filters.

MEMORY: Non-volatile memory for storage of 2 setups.

CONTROL: Front-panel, OSD, RS-232 and Ethernet; video pane size and position; video ProcAmp

functions: video zoom, freeze.

POWER CONSUMPTION: 5V DC, 560mA.

DIMENSIONS: 21.5cm x 17.7cm x 4.4cm (8.5" x 7" x 1.7") W, D, H.

WEIGHT: 0.8kg (1.76lbs) approx.

INCLUDED Power supply, RC-IR3 Infrared Remote Control, rack "ears".

ACCESSORIES:

OPTIONS: RK-1 19" rack adapter.

