RC-2

Wall Plate – RS−232 Controller

The RC−2 is a 2−button controller that sends a series of RS−232 commands with the push of a button. It operates serial devices such as projectors, displays & switchers.

FEATURES

- 2 Back Lit & Label Capable Buttons.
- 1 RS-232 Port - Controls a device via serial control protocols.
- Optional Ports - Add control ports with the PL−18 Control Port Expander.
- Memory - Each button can be programmed with up to four macro sequences.
- Dimensions - 7.9cm x 1.59cm x 12.4cm (3.12" x 0.63" x 4.88") US; 8.6cm x 1.59cm x 8.6cm (3.39" x 0.63" x 3.39") and 8cm x 1.59cm x 8cm (3.15" x 0.63" x 3.15") EU W, D, H.
- Wall Plate Size - 1 gang EU/US.

RC-2

TECHNICAL SPECIFICATIONS

PORT:	1 RS−232 on a terminal block connector.
POWER CONSUMPTION:	12V DC, 40mA.
DIMENSIONS:	7.9cm x 1.59cm x 12.4cm (3.12" x 0.63" x 4.88") US; 8.6cm x 1.59cm x 8.6cm (3.39" x 0.63" x 3.39") and 8cm x 1.59cm x 8cm (3.15" x 0.63" x 3.15") EU W, D, H.
WEIGHT:	0.3kg (0.67lbs) approx.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK−121WP 19" rack adapter, RS−232 9−pin D−sub port to 3−pin terminal block connector cable.