


## RC-63DL

6-Button Room Controller with Digital Volume Control & LCD Group Labels





The RC-63DL is a 6-button room controller with a digital volume knob for multimedia rooms. The unit can control audio components, video components and other room facilities such as lights and screens.

## FEATURES

- 6 Programmable Buttons Color, back-lit & label capable.
- Programmable Back-Lit LCD Group Labels For printed group labels, order the RC-62D.
- Digital Volume Control Knob. For use with SummitView only.
- Macro Capability Carries out multiple commands with a single press of a button.
- Command Banks Each button offers multiple layers of functions for alternate behavior, toggle functionality, and more.
- Internal Clock Schedules recurring tasks, defines system shutdown timer for economic operation, and more.
- 1 USB For programming.
- **1** Bidirectional RS-232 Controls AV equipment such as projectors, LCD and PDP displays, power amplifiers, switchers and scalers.
- 1 IR Output Additional control port for AV equipment.
- IR Learning Function Learns commands from IR remotes.
- <sup>2</sup> 2 Relay Contact Closure Ports Conveniently controls other room items related to the AV system such as raising and lowering drapes, the screen or the projector.
- <sup>■</sup> 2 K-Net<sup>TM</sup> Connectors Connects to other control panels or a central control processor.
- K-Net Control Channel Provides power and control data to the wall plate controllers over a single cable.
- Wall Plate Size 2 gang. Available in white.



## RC-63DL

## TECHNICAL SPECIFICATIONS

| PORTS:<br>OUTPUT:        | 1 RS-232 on terminal block connectors; 2 K-NET on terminal block connectors; 1 USB port.<br>2 relays on terminal block connectors (36V AC or DC, 2A, 60V AC maximum on non-inductive |
|--------------------------|--|
| POWER                    | load); 1 IR emitter on terminal block connectors.<br>12V DC, 140mA.  |
| CONSUMPTION:<br>FUSE:    | 500mA, FSMD 2920.  |
| ADAPTER:                 | SummitView™ kits: 12V, 5A; independent: 12V, 500mA.  |
| DIMENSIONS:<br>WEIGHT:   | 11.4cm x 2.9cm x 11.4cm (4.49" x 1.14" x 4.49") W, D, H.<br>0.14kg (0.31lbs) approx.   |
| INCLUDED<br>ACCESSORIES: | USB cable 0.91m (3ft), screwdriver, Windows®-based Kramer control software.  |
| OPTIONS:                 | RK-2WP 19" rack adapter.   |