



## RC-76R

### 6-Button Room Controller



The RC-76R is a six-button configurable room controller for multimedia rooms. It controls audio components, video components and other room facilities such as lights and screens.

Requires K-Config Software 2.0 - Available Oct 2013

#### FEATURES

- **6 Configurable Buttons** - RGB backlit, front panel buttons, configured using the K-Config configuration software.
- **1 GPI/O Port** - Can be configured by K-Config as a digital input, digital output or analog input for interfacing with a variety of devices such as sensors, switches, LEDs, or relays.
- **2 Bidirectional RS-232 Ports** - Control AV equipment such as projectors, LCD and PDP displays, power amplifiers, switchers and scalers.
- **2 Relay Contact Closure Ports** - Control other room items related to the AV system, such as, raising and lowering drapes, a screen or a projector.
- **2 IR Control Ports** - With an IR learning receiver behind the front plate that learns commands from any IR remote.
- **1 RS-485 Port.**
- **Kramer Site-CTRL Compatibility** - For network remote control and management over the Ethernet port.
- **K-NET™ Control Channel** - Connects compatible user interfaces, supply power and control data over a single cable.
- **Flexible Control** - Via Ethernet and K-NET.
- **Wall Plate Size** - 1 gang US, Decora compatible. Suitable for installation in TBUS-1Ax1.



## RC-76R

### TECHNICAL SPECIFICATIONS

**INPUTS:** 2 RS-232, 1 RS-485, 1 GPI/O and 1 K-NET on terminal block connectors; 1 Ethernet on an RJ-45 connector; 1 USB for programming.

**OUTPUTS:** 2 IR, 2 relays (36V AC or DC, 2A, 60VAC maximum on non-inductive load) and 1 GPI/O on terminal block connectors.

**DEFAULT IP SETTINGS:** IP number – 192.168.1.39; Mask – 255.255.0.0; Gateway – 0.0.0.0.

**POWER CONSUMPTION:** 12V DC, 260mA.

**OPERATING TEMPERATURE:** 0° to +40°C (32° to 104°F).

**STORAGE TEMPERATURE:** -40° to +70°C (-40° to 158°F).

**HUMIDITY:** 10% to 90%, RHL non-condensing.

**DIMENSIONS:** 7.9cm x 2.8cm x 12.4cm (3.1" x 1.1" x 4.9") W, D, H (with wall plate).

**WEIGHT:** 0.6kg (1.4lbs) approx.

**INCLUDED ACCESSORIES:** Power supply, black and white front plates, black and white Decora frames.

