



TP-10

Composite Video, s-Video & Stereo Audio over Twisted Pair Receiver with IR Repeater



The TP-10 is a twisted pair receiver for composite or s-Video (Y/C) signals and unbalanced analog stereo or S/PDIF digital audio signals. The TP-9 transmitter converts the video and audio to a twisted pair signal and the TP-10 converts the twisted pair signal back into video & audio signals.

FEATURES

- Bandwidth - >70MHz (-3dB).
- Audio - S/PDIF or unbalanced analog.
- IR Repeater - 1 IR sensor.
- Twisted Pair Input/Outputs - RJ-45 connector.
- System Range - up to 200m (650ft).
- Cable - UTP (unshielded twisted pair) or STP (shielded twisted pair) such as CAT 5.
- Level (Gain) & EQ (Peaking) Controls.
- Power Connect™ System - Only one unit in a system, the transmitter or the receiver needs to be connected to a power source when the devices are within 50m (150ft) of each other.
- Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



TP-10

TECHNICAL SPECIFICATIONS

INPUT:	1 RJ-45 CAT 5 shielded connector (LINE IN).
OUTPUT:	1 composite video 1Vpp/75Ω on a BNC connector; 1 s-Video 1Vpp/75Ω [Y], 0.3Vpp/75Ω [C] on a 4-pin connector; 1 S/PDIF (digital audio) on an RCA connector; 1 audio (analog audio) <8dBu on a 3.5mm mini connector.
MAX. OUTPUT LEVEL:	Video: 2.6V; Audio: 4.6Vpp.
BANDWIDTH:	Video: >70MHz/-3dB; Audio: 20Hz to 20kHz/0.1dB.
NON-LINEARITY:	<0.05%.
DIFF. GAIN:	<0.05%.
DIFF. PHASE:	0.09Deg.
S/N RATIO:	Video: >75dB/5MHz weighted; Audio: >73dB.
AUDIO CONVERSION	48kHz.
SAMPLE RATE:	
AUDIO CONVERSION	24-bits.
RESOLUTION:	
POWER CONSUMPTION:	12V DC, 82mA.
DIMENSIONS:	12cm x 6.95cm x 2.76cm (4.7" x 2.8" x 1.08") W, D, H.
WEIGHT:	0.3kg (0.67lbs) approx.
OPTIONS:	RK-3T 19" rack adapter.

