



TP-573

HDMI, Bidirectional RS-232 & IR over Twisted Pair Transmitter



The TP-573 is a DGKat™ twisted pair transmitter for HDMI, bidirectional RS-232 and infrared signals. The TP-573 converts the input signals to a twisted pair signal and the TP-574 converts it back to HDMI, RS-232 and infrared signals.

FEATURES

- **Max. Data Rate** - 4.95Gbps (1.65Gbps per graphic channel).
- **HDTV Compatible.**
- **HDCP Compliant.**
- **DGKat™ Signal Integration** - Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables. We strongly recommend using Kramer DGKat™ cables designed specifically for optimum performance.
- **HDMI Support** - x.v.Color™, Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD.
- **3D Pass-Through.**
- **EDID PassThru** - Passes EDID signals between the source and display.
- **Bidirectional RS-232 & IR Interface.** - 38400 max baud rate.
- **System Range** - Up to 90m (295ft) at 1080i, or up to 30m (98ft) at 1080p on shielded BC-DGKat524 cable. Up to 90m (295ft) at 1080i, or up to 70m (230ft) at 1080p on shielded BC-DGKat623 cable. Up to 100m (330ft) at 1080i or up to 90m (295ft) at 1080p on shielded BC-DGKat723 cable.
- **Cable** - Requires shielded twisted pair (STP) cable. For optimum range and performance use, use Kramer's BC-DGKat524, BC-DGKat623 and BC-DGKat723 cables. Note that the transmission range depends on the signal resolution, graphics card and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground.
- **Power Connect System™** - A single connection to the transmitter powers both units.
- **Compact DigiTOOLS®** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



TP-573

TECHNICAL SPECIFICATIONS

| | |
|--------------------------------|---|
| INPUTS: | 1 HDMI connector, 1 bidirectional IR port on a 3.5mm mini jack, 1 bidirectional RS-232 port on a 9-pin D-sub connector. |
| OUTPUTS: | 1 CAT 5 OUT on an RJ-45 connector. |
| BANDWIDTH: | 4.95Gbps (1.65Gbps per graphic channel). |
| COMPLIANCE WITH HDMI STANDARD: | Supports HDMI and HDCP. |
| POWER CONSUMPTION: | 12V DC, 510mA. |
| DIMENSIONS: | 12.1cm x 7.18cm x 2.42cm (4.76" x 2.83" x 0.95"), W, D, H. |
| WEIGHT: | 0.3kg (0.67lbs) approx. |
| INCLUDED ACCESSORIES: | 12V DC power supply. |
| OPTIONS: | RK-3T 19" rack mount, Kramer remote external receiver, Kramer BC DGKat524 (CAT 5 24AWG) and BC DGKat623 (CAT 6 23AWG) cables. |

