



TR-1

Video Isolation Transformer



The TR-1 is a high-resolution isolation transformer for composite video signals. It completely isolates devices to eliminate video hum, ground loops, and DC offsets that can degrade picture quality.

FEATURES

- Bandwidth - 5.8MHz (-3dB).
- Passive Device - No power required.
- Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3TR rack adapter.



TR-1

TECHNICAL SPECIFICATIONS

INPUT:	1 composite video, 1Vpp/75Ω on a BNC connector.
OUTPUT:	1 composite video, 1Vpp/75Ω on a BNC connector.
INSERTION LOSS:	0.8dB.
MAX. OUTPUT LEVEL:	4Vpp/75Ω.
BANDWIDTH (-3dB):	5.8MHz.
DIFF. GAIN:	0.05%.
DIFF. PHASE:	0.05Deg.
K-FACTOR:	1.2%.
S/N RATIO:	73.4dB.
TILT:	0.1%.
NON-LINEARITY:	0.1%.
COUPLING:	Transformer.
POWER CONSUMPTION:	None, passive device.
DIMENSIONS:	12cm x 7.3cm x 3cm (4.7" x 2.88" x 1.2") W, D, H.
WEIGHT:	0.34kg (0.75lbs) approx.
INCLUDED ACCESSORIES:	Mounting brackets.
OPTIONS:	RK-3TR 19" rack adapter.

