



## VA-2H

### HDMI EDID Reader-Emulator

---



The VA-2H is a diagnostic and debugging tool for installers working with HDMI devices. The unit can switch three different EDIDs to the HDMI input. The installer can manipulate various parameters of the EDID using a software editor and the EDID can be downloaded over the USB connection.

### FEATURES

---

- **Max. Data Rate** - 6.75Gbps (2.25Gbps per graphic channel).
- **Input Resolution** - Up to 1080p.
- **Standards Compliance** - HDCP 1.1, and DVI 1.0.
- **HDMI Support** - Deep Color, x.v.Color™, Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD.
- **I-EDIDPro™ Kramer Intelligent EDID Processing™** - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- **Indicators** - Input, output, USB and HDCP LEDs.
- **Non-Volatile Memory** - Saves final settings.
- **Compact DigiTOOLS®** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



## VA-2H

### TECHNICAL SPECIFICATIONS

INPUT:	1 HDMI connector.
OUTPUTS:	1 HDMI connector, 1 S/PDIF digital audio on an RCA connector.
PORT:	1 USB connector.
BANDWIDTH:	6.75Gbps (2.25Gbps per graphic channel).
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
RESOLUTION:	Up to UXGA; 1080p, 36bit.
POWER CONSUMPTION:	12V DC, 410mA.
CONTROLS:	SELECT button, EDID MODE LEDs.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	12cm x 7.2cm x 2.4cm (4.7" x 2.8" x 1.0") W, D, H.
WEIGHT:	0.3kg (0.7lbs).
INCLUDED ACCESSORIES:	Power supply, Windows®-based control software.
OPTIONS:	RK-3T 19" rack adapter.

