

VM-20ARII

1:20 Composite Video & Stereo Audio Distribution Amplifier







The VM-20ARII is a multi-format, high-performance distribution amplifier that can also be configured for composite video and unbalanced stereo audio signals. It can be configured as a 1:10 distribution amplifier for s-Video (Y/C) signals or a 1:5 distribution amplifier for RGBS signals, both with unbalanced stereo audio.

FEATURES

- High Bandwidth 430MHz (-3dB).
- Muti-Mode Configure as a 1:20 (composite), 1:10 (s-Video), or 1:5 (RGBS) DA.
- Grouped Audio Level Control.
- Grouped Level (Gain) and EQ (Peaking) Controls.
- Looping Input.
- Selectable Input Signal Termination.
- Video AC/DC Coupling Selection.
- Standard 19" Rack Mount Size 2U.

VM-20ARII

TECHNICAL SPECIFICATIONS

INPUTS: 4 video with loop, $1Vpp/75\Omega$ on BNC connectors with termination switches; 4 unbalanced stereo

or balanced mono audio, $+4dBu/50k\Omega$ on RCA connectors.

OUTPUTS: 20 video (1:20, 2x1:10, 4x1:5, 1:10, 2x1:5), $1Vpp/75\Omega$ on BNC connectors; 20 unbalanced stereo

or balanced mono audio (1:20, 2x1:10, 4x1:5, 1:10, 2x1:5), +4dBu/50Ω 27Vpp max. on RCA

connectors.

VIDEO BANDWIDTH 430MHz.

(-3dB):

AUDIO BANDWIDTH 110kHz.

(-3dB):

DIFF. GAIN: 0.06%.
DIFF. PHASE: 0.08 Deg.
VIDEO S/N RATIO: 76dB.
AUDIO S/N RATIO: 80dB.

VIDEO CONTROL: −1.2 to +1.7dB level, 0 to +2.4dB EQ.

AUDIO CONTROL: +0.3 to +6.2dB.

VIDEO COUPLING: DC/AC user selectable. AUDIO COUPLING: AC (input), DC (output).

AUDIO THD+NOISE: 0.02%. 2nd HARMONIC: 0.002%.

POWER 230V AC 50/60Hz (115V USA) 18.5VA.

CONSUMPTION:

DIMENSIONS: 19" x 7" x 2U W, D, H, rack mountable.

WEIGHT: 3.6kg (7.9lbs) approx.

INCLUDED Power cord.

ACCESSORIES:

