



VM-2HxI

1:2 HDMI Distribution Amplifier



The VM-2HxI is a distribution amplifier for HDMI signals. The unit reclocks and equalizes the signal and distributes it to two identical outputs.

FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliant.
- HDMI Support - Deep Color, x.v.Color™, Lip Sync, CEC.
- 3D Pass-Through.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal integrity to travel longer distances.
- Active Output LED.
- Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



VM-2HxI

TECHNICAL SPECIFICATIONS

INPUT:	1 HDMI connector.
OUTPUTS:	2 HDMI connectors.
MAX. DATA RATE:	6.75Gbps (2.25Gbps per graphic channel).
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
CONTROLS:	EDID SETUP button, input select button.
INDICATOR LEDs:	IN 1, IN 2, OUT 1, OUT 2, and ON LEDs.
POWER CONSUMPTION:	5V DC, 910mA.
DIMENSIONS:	12cm x 7.2cm x 2.4cm (4.7" x 2.8" 1.0") W, D, H.
WEIGHT:	0.3kg (0.67lbs) approx.
INCLUDED ACCESSORIES:	Power supply, bracket installation kit.
OPTIONS:	RK-3T 19" rack adapter.

