



VM-3SN

1:3 s-Video Distribution Amplifier



The VM-3SN is a high-performance distribution amplifier for s-Video (Y/C) signals. The unit takes one s-Video input and distributes the signal to three identical outputs.

FEATURES

- Bandwidth - 135MHz (-3dB).
- Selectable Input Signal Termination.
- Y & C Level (Gain) Controls.
- Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



VM-3SN

TECHNICAL SPECIFICATIONS

INPUT:	1 composite video on a BNC connector.
OUTPUTS:	3 composite video on BNC connectors.
MAX. OUTPUT LEVEL:	1.8Vpp.
BANDWIDTH (-3dB):	135MHz.
DIFF GAIN:	0.12%.
DIFF PHASE:	0.03Deg.
K-FACTOR:	<0.05%.
S/N RATIO:	74.3dB.
CONTROL:	Y-level: -1.6 to +6.3dB; C-level: -0.4 to +7.6dB.
COUPLING:	AC.
POWER CONSUMPTION:	12V DC, 27mA.
DIMENSIONS:	11.7cm x 6cm x 3.2cm (4.6" x 2.4" x 1.3") W, D, H.
WEIGHT:	0.28kg (0.62lbs) approx.
INCLUDED ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.

