

VM-400HDCP

1:4 DVI (HDCP) Distribution Amplifier



FEATURES

- Max. Data Rate 4.95Gbps (1.65Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliant.
- Kramer Equalization & re-Klocking[™] Technology Rebuilds the digital signal to travel longer distances.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- EDID Acquisition Default, single output or all connected outputs (auto-mix).
- Controls EDID Read and Select buttons.
- Active Input & Output LED Indictors.
- Compact MegaTOOLS[™] 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-T2B universal rack adapter.



VM-400HDCP

TECHNICAL SPECIFICATIONS

INPUT:	1 DVI-I (F) connector.
OUTPUTS:	4 DVI-I (F) connectors.
MAX. DATA RATE:	4.95Gbps (1.65Gbps per graphic channel).
COMPLIANCE WITH STANDARD: HDCP.	
CONTROLS:	SELECT and READ buttons for selecting and storing EDID information.
INDICATOR LEDs:	OUTPUTS 1 to 4 and power LEDs.
POWER CONSUMPTION:	5V DC, 450mA.
DIMENSIONS:	18.8cm x 11.27cm x 2.57cm (7.4" x 4.44" x 1.01") W, D, H.
WEIGHT:	0.42kg (0.93lbs) approx.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-T2B 19" rack adapter.

