



VM-4DP

1:4 DisplayPort Distribution Amplifier



The VM-4DP is a high-quality distribution amplifier for DisplayPort signals. The unit distributes one input signal to four identical outputs.

FEATURES

- Max. Data Rate - 10.8Gbps (2.7Gbps per lane).
- Max. Resolution - 2560x1600 @60Hz.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for DisplayPort systems.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.
- HDTV Compatible.
- HDCP Compliant.
- Worldwide Power Supply - 100-240V AC.
- Standard 19" Rack Mount Size - 1U. Rack "ears" included.



VM-4DP

TECHNICAL SPECIFICATIONS

INPUT:	1 DisplayPort connector.
OUTPUTS:	4 DisplayPort connectors.
MAX. DATA RATE:	10.8Gbps (2.7Gbps per lane).
COMPLIANCE WITH HDMI STANDARD:	Supports DisplayPort 1.1a and HDCP 1.3.
CONTROLS:	EDID Select and Read buttons.
INDICATORS:	Power, Active and 4 output LEDs.
POWER CONSUMPTION:	100–240V AC.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	19" x 7" x 1U W, D, H.
WEIGHT:	2.5kg (5.5lbs) approx.
INCLUDED ACCESSORIES:	Power cord, rack "ears".

