



VP-311DVI

3x1 DVI (HDCP), Stereo & S/PDIF Audio Standby Switcher



The VP-311DVI is a high-performance switcher for DVI-D video, stereo and S/PDIF audio signals. When configured as a standby switcher, the selected input switches to the next highest priority input if the signal is interrupted.

FEATURES

- Max. Data Rate - 4.95Gbps (1.65 Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliant.
- HDMI Support - HDMI Compressed Audio Channels.
- Input/Output - DVI-D signals (on a DVI-I connector).
- Standby Switching Priority - User-definable via DIP-switches.
- Flexible Control Options - Front panel, RS-232, IR remote (included), contact closure & Ethernet.
- Desktop Size - Compact Size. Two units can be mounted side-by-side in a 1U rack space with the optional RK-1 adapter.



VP-311DVI

TECHNICAL SPECIFICATIONS

INPUTS:	3 DVI, 1.2Vpp on DVI Molex 24-pin female connectors; DDC signal 5Vpp (TTL); 3 S/PDIF digital audio on RCA connectors; 3 unbalanced stereo audio +4dBu on 3.5mm mini jacks.
OUTPUTS:	1 DVI, 1.2Vpp on a DVI Molex 24-pin female connector; DDC signal 5Vpp (TTL); 1 S/PDIF digital audio on an RCA connector; 1 unbalanced stereo audio +4dBu on a 3.5mm mini jack; 1 balanced stereo audio on a 5-pin detachable terminal block.
DATA RATE:	4.95Gbps (1.65 Gbps per graphic channel).
CONTROLS:	Front panel buttons, infrared remote control transmitter, RS-232, Ethernet.
POWER CONSUMPTION:	12V DC, 390mA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	21.6cm x 16.1cm x 4.4cm (8.5 x 6.3 x 1.7) W, D, H.
WEIGHT:	1.2kg (2.6lbs) approx.
INCLUDED ACCESSORIES:	Power supply, DVI male to male cable, IR remote control transmitter, null-modem adapter, Windows®-based Configuration Manager (Ethernet Configuration and Virtual Serial Port) CD.
OPTIONS:	RK-1 19" rack adapter.

