

VS-55A

5x1 Stereo Audio Switcher







The VS-55A is high-performance switcher for unbalanced stereo audio signals. It switches any one of five signals to a single output.

FEATURES

- S/N Ratio >78dB.
- Control Front panel & contact closure (via link connector).
- Desktop Size Compact size. 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-1 adapter.

VS-55A

TECHNICAL SPECIFICATIONS

 $\label{eq:connectors} \begin{tabular}{ll} INPUTS: & 5 unbalanced stereo audio, $1Vpp/50k\Omega$ on RCA connectors. \\ OUTPUT: & 1 unbalanced stereo audio, $1Vpp/100\Omega$ on RCA connectors. \\ \end{tabular}$

MAX AUDIO OUTPUT: 3Vpp. AUDIO BANDWIDTH (-3dB): 100kHz.

GAIN RANGE: 60dB (via underside accessible trimmers).

AUDIO S/N RATIO: Better than 78dB.

CONTROL: 5 front panel buttons, contact closure via the link connector.

THD: Less than 0.08%. POWER CONSUMPTION: 12V DC, 100mA.

DIMENSIONS: 16.5cm x 12cm x 4.5cm (6.5" x 4.7" x 1.8") W, D, H.

WEIGHT: 0.62kg (1.4lbs) approx.

INCLUDED ACCESSORIES: Power supply.

OPTIONS: RK-1 19" rack adapter.

