



VS-801USB

8x1 USB 2.0 Switcher



The VS-801USB is a high-quality 8x1 USB switcher. It accepts up to eight USB devices and switches the selected device to the host.

FEATURES

- **High-Speed USB** - Ver 2.0.
- **Flexible Control Options** - Front panel buttons, RS-232 and Ethernet via K-SINGLE control application software, remote contact closure, IR remote (included).
- **Firmware Upgrade** - Via RS-232 using K-UPLOAD application software.
- **Compact MegaTOOLS™** - 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-T2B universal rack adapter.



VS-801USB

TECHNICAL SPECIFICATIONS

DEVICE PORTS:	8 USB, type A.
HOST PORT:	1 USB, type B.
CONTROL:	Front panel buttons, IR remote control, RS-232, Ethernet, remote contact closure terminal block.
POWER CONSUMPTION:	5V DC, 150mA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	18.8cm x 11.4cm x 2.4cm (7.4" x 4.5" x 0.9") W, D, H.
WEIGHT:	0.75kg (1.7lbs) approx.
INCLUDED ACCESSORIES:	Power supply, bracket installation kit, 1m hi-speed USB cable.
OPTIONS:	RK-T2B 19" rack adapter.

