


DC ENCODED PINOUT

- PIN 1 = MOTOR CH A  
PIN 2 = FAR LIMIT  
PIN 3 = N/C  
PIN 4 = +5Vdc  
PIN 5 = MOTOR +  
PIN 6 = MOTOR CH B  
PIN 7 = NEAR LIMIT  
PIN 8 = COMMON  
PIN 9 = MOTOR -



USED ON: MATERIAL:		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	P/N SUFFIX DEFINITION -1 CONVERSION COATING -2 PAINTING -3 MARKING -R REWORK	THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR, ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR	 ROCHESTER, NEW YORK
FINISH:		TOLERANCES: DEC. .XXX ± .005 DEC. .XX ± .010 FRACT. ± 1/64 ANGLES ± 30' CONCENTRICITY .003 TIR BREAK ALL SHARP EDGES .005 MIN. .010 MAX MAX. SURF. ROUGHNESS 32	SCALE: 1:1 DR.: R. PODLENA CH.: P. BONAFEDE APP.: DATE DR.: 9/18/2003 DO NOT SCALE DRAWING		
CHAMFER ALL THREADS 30° TO ROOT DIAM.				 0.0 inch 1.0 0.0 mm 25.0	MOTORIZED (ENC) 12X ULTRA w/ 2
				 B	AUDIOVIDEO SUPPLY 1-800-284-2288 sales@avsupply.com www.avsupply.com