


**DC ENCODED PINOUT**

- PIN 1 = MOTOR CH A
- PIN 2 = FAR LIMIT
- PIN 3 = N/C
- PIN 4 = +5Vdc
- PIN 5 = MOTOR +
- PIN 6 = MOTOR CH B
- PIN 7 = NEAR LIMIT
- PIN 8 = COMMON
- PIN 9 = MOTOR -



**OUTLINE**

<b>USED ON:</b> <b>MATERIAL:</b>  <b>FINISH:</b>  CHAMFER ALL THREADS 30° TO ROOT DIAM.	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	<b>P/N SUFFIX DEFINITION</b> -1 CONVERSION COATING -2 PAINTING -3 MARKING -R REWORK	THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR, ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR	 ROCHESTER, NEW YORK
	<b>TOLERANCES:</b> DEC. .XXX ± .005 DEC. .XX ± .010 FRACT. ± 1/64 ANGLES ± 30° CONCENTRICITY .003 TIR BREAK ALL SHARP EDGES .005 MIN. .010 MAX MAX. SURF. ROUGHNESS 32	<b>SCALE:</b> 1:1 <b>DR.:</b> R. PODLENA <b>CH.:</b> P. BONAFEDE <b>APP.:</b> <b>DATE DR.:</b> 9/16/2003 <b>DO NOT SCALE DRAWING</b>		

**AUDIOVIDEO SUPPLY**  
 1-800-284-2288 sales@avsupply.com  
 www.avsupply.com

For design help, accessories or pricing, please contact:  
 sales@avsupply or call: 1-858-565-1101

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com