



Lens Specifications - NMV - 8			
Specifications	Value	1/2"	1/3"
Focal Length	f = 8mm		
Maximum diameter (Ratio)	F = 1.4:1 ~ 16 ~ Close		
Element	6 gp. 7 Element		
Picture Size	6.6 x 8.8mm	4.8 x 6.4mm	3.6 x 4.8 mm
Angle - Vertical	47.7 deg.	34.6 deg.	28.6 deg.
Horizontal	64.2 deg.	46.2 deg.	34.5 deg.
Diagonal	81.3 deg.	58.1 deg.	43.3 deg.
Distortion	-6.2%	-2.5%	-1.3%
Shooting Range - Vertical	184mm	129.3mm	95.5mm
At Minimum - Horizontal	260mm	177.5mm	129.3mm
Focus Distance - Diagonal	356mm	231.0mm	165.1mm
Minimum Focus Distance	0.1m		
Flange Back	17.526mm in air		
Back Focus	11.3mm in air		
Filter Screw Size	m27.0 X 0.5		
Effective Diameter - Front	17.4mm dia.		
- Rear	11.1mm dia.		
Mount	C-Mount		
Exit Pupil	-30.2mm dia.		
Temperature Range	- 10 ~ + 45 deg. C		
Strong Temperature Range	- 40 ~ + 60 deg. C		
Resolution - Center	100 Line/mm		
- Corner	40 Line/mm		

## OUTLINE

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR, ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR	 ROCHESTER, NEW YORK
	SCALE: 1.5:1	
WEIGHT: See Table		 1-800-284-2288 sales@avsupply.com www.avsupply.com
DR: BE	DO NOT SCALE DRAWING	
CH:		SIZE B
PROJECT #: E2338		
DATE DR: 7/13/2007		

For design help, accessories or pricing, please contact:  
 sales@avsupply or call: 1-858-565-1101

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com