

LED Monitor **21REDB** Display

ORION IMAGES CORPORATION



SPECIAL FEATURES-

The ORION LCD w/ LED BLU (backlight unit) high brightness displays are a truly professional experience in next generation technology using eco-friendly material (no mercury or halogen). This technology exceeds the NTSC color gamut standard of 100% with the LED BLU at 123% to provide a wider range of colours than ever before – you will see colors on screen as you see them in real world.

- 1920 x 1080p Full HD
- LED BLU (Back Light Unit) Display Monitor
- DVI-D 1 In / VGA 1 In, PC Strero 1 In
- 5ms Response, 300 NITS
- 1000:1 Contrast Ratio
- Auto Color Balance Function
- VESA Mount Compatible
- Wall and Ceiling Mount



DIMENSIONS

21.06"

OTHER VIEW



 \Box istributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

1.417



7300 Bolsa Avenue, Westminster, CA 92683 = Tel. 714.766.6300 = Fax. 714.766.6310 = www.orionimages

1-800-284-2288 sales@avsupply.com www.avsupply.com

AUDIOVIDEOSUF

Side View

For design help, accessories or pricing, please contact: sales@avsupply or call: 1-858-565-1101

SPECIFICATIONS

		21REDB
Display	Screen Size	21.5 Inch
	Panel Type	LED BLU
	Max. Resolution	1920 x 1080 @ 60Hz
	Pixel Pitch	0.24825 x 0.24825 mm
	Brightness	300cd/m ²
	Contrast Ratio	1000 : 1
	Aspect Ratio	16 : 9
	Viewing Angle (H/V)	170'/ 160°
	Display Color	16.7 Million
	Response Time	< 5ms
	Video System	NTSC / PAL
Interface	DVI-D In	1
	VGA In (15Pin D-Sub)	1
	PC Strero In	1
Audio	Built-In Speaker	Yes (2W x 2)
Features	Auto Color Balance	Yes
	Multi Language	English, Dutch, Spanish, French, Korea
Dimension (W x H x D)	Outline Dimension (w/ stand)	21.06" x 15.51" x 1.417"
	Net. Weight	3.99Kg (8.818 lbs)
Cabinet	Material / Color	ABS Plastic / Black
	Desk Top Stand	Yes
	Tilt Function	Yes
Warranty	Part / Labor	2year / 2year
	MTBF (Approx.)	30,000 Hours
Regulations		RoHS, UL, FCC (A), TUV/GS, CE, RRL
Power	Consumption: < On	< 30W
	Electrical Ratings	AC110 ~ 230V(50/60Hz)
		DC12V / 3.7A
Circumstance	Operating Temperature	0 ~ 50°C / 32 ~ 122°F
	Storage Temperature	-20 ~ 60°C / -4 ~ 140°F
Mounts	VESA [™] Mount Size	75 x 75mm
	Wall	WB-5, WB-10, WB-30, WB-31
	Ceiling	CMK-01
*Design and specifications are subject to change without notice		