



OIC-7002

HIGH PERFORMANCE BROADCAST RACK MOUNT MONITOR



The ORION Images introduces a dual 7 inch high performance, rack mount ready, professional broadcast monitor that features SD-SDI / HD-SDI / 3G-SDI Multi-Format Signal Inputs, 800 x 480 with LED Back Light panel resolution, Title Generator, Embedded Audio Level Indicators up to 16ch, Waveform Display, Vector Scope and many of the other advantages as higher level broadcast display offerings.



SPECIAL FEATURES

- Panel Resolution 800 x 480 with LED Back Light
- SMPTE Standards SD-SDI/HD-SDI/3G-SDI is applied.
 - SD-SDI - 480i/59.94, 576i/50
 - HD-SDI - 1080i 60/59.94/50, 1080p 30/29.97/25/24/24sf/23.98/23.98sf, 720p 60/59.94/50/30/29.57/25/24/23.98
 - 3G-SDI - 1080p 60/59.94/50
- Loop-Through
- Title Generator
- Remote & Tally - DSUB15
- Embedded Audio Level Indicators up to 16ch
- Time Code Indicator
- Waveform Display
- Vector Scope Display
- Various Controls- Brightness, Contrast, Chroma, Aperture, HV Delays, Aspect Ratio, Scan Size, Area Markers, Safety Markers, Mono/Color, Color Temperatures
- Low Profile - 3RU
- Tilt Mechanism up to 90 Degrees with small depth
- AC Power 90V to 240V with AC Adaptor thru XLR Connector



Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

GSA Contract No. GS-03F-0152X

For design help, accessories or pricing, please contact: sales@avsupply or call: 1-858-565-1101

AUDIOVIDEO SUPPLY
 1-800-284-2288 sales@avsupply.com
 www.avsupply.com

OIC-7002

HIGH PERFORMANCE BROADCAST RACK MOUNT MONITOR



SPECIFICATIONS

| OIC-7002 | |
|------------------------|---|
| Panel | 7 Inch x 2 (Dual Monitor) |
| Resolution | 800 x 480 Pixels |
| Pixel Pitch | 0.1905mm x 0.1905mm |
| Display Area | 152.4mm x 91.4mm |
| Color | 16.7 Million |
| Brightness | 280 cd/m ² |
| Contrast | 400 : 1 |
| Backlight | LED |
| Video Interface | BNC In / Out x 1 |
| Video Format | SD-SDI / HD-SDI / 3G-SDI |
| Tally & Remote | DSUB15 |
| Aspect Ratio | 16:9 or 4:3 |
| H / V Display | H only, V only, H and V |
| Marker | Various Area and Safety Markers |
| Audio Level Indicators | 16ch |
| Tally | Yes |
| Title Generator | Up to 8 characters |
| Mono / Color | Yes |
| Time Code | Yes |
| Waveform | Yes |
| Vector Scope | Yes |
| Color Temperature | 6500° K or 9300° K |
| Rack Height | 3RU |
| Tilt Mechanism | Up to 90 Degrees |
| Power Requirement | 100VAC to 240VAC (with AC Adaptor, XLR Connector) |
| Power Consumption | Less than 20W |

*Design and specifications are subject to change without notice




LESS SPACE DESIGN

ORION Images OIC-7002 Broadcast Rack Mount monitor has a capability of tilt 90 degree.



OPERATION FEATURES




WAVEFORM

Waveform display is provided as standard. Size, position, layout etc can be selected in the OSD menu.

VECTOR SCOPE

Vector Scope display is provided as standard. Size, position, layout etc can be selected in the OSD menu



AUDIO LEVEL INDICATOR (Embed Audio)


Maximum 16 channels can be displayed on the top of the screen.

TITLE GENERATOR

Up to 8 characters (alphabets and numbers) can be inserted at lower position on the screen



DIMENSIONS



ORION IMAGES INCORPORATION
7300 Bolsa Avenue, Westminster, CA 92683
Tel. 714.766.6300 / Fax. 714.766.6310 / www.orionimages.com
©ORION Images Incorporation. All rights reserved. ver. 111208-1.2



Contract No. GS-03F-0152X

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101