

Pan and Tilt your Camera Samsung Positioning System

SAMSUNG

Camera and lens not included



Positioning System

SCU-VAC/VAC1


SAMSUNG

The SCU-VAC and SCU-VAC1 are integrated positioning systems that accept various camera/lens combinations to provide high speed pan & tilt. They offer continuous 360° rotation with an extended -85° to 40° tilt range. Internal positioning encoders allow for all 255 prepositions to be accurate within 0.1° even in high wind/vibration environments. These units are rated for weatherproof protection (IP 66) and have an operating temperature range of -58° to 122°F (-50° to 50°C), making them an ideal solution for demanding outdoor applications such as traffic or critical infrastructure.

- Integrated Receiver, Pan/ Tilt, and Housing
- Position encoders for absolute positioning
- 360° Continuous Pan Rotation
- Tilt Range of +40° to -85°
- Accepts most 24VAC 3rd party Cameras
- Wiper included


Positioning System J-VAC/VAC1 +50°C -50°C **RS-485 360**° PT

Specifications



Dimensions

Unit : mm (inch)



Accessories



SAMSUNG	

SAMSUNG TECHWIN AMERICA Inc. 100 Challenger Road, Suite 700, Ridgefield Park, NJ 07660, UNITED STATES Tol Free : 1-877-213-1222 Fax : 1-201-373-0124 www.samsungsecurityusa.com



The Eco mark represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive. Design and specifications are subject to change without notice. DISTRIBUTED BY