



NSBKDH05

Decoder/Display
accelerator board

\$1,390.00

U.S.List Price

UPC: 027242278639

Overview

Highlights

- * Maximum Decoding Resolution Up to 1,920 x 1,080
- * Video Decoding Format *5 H.264/MPEG-4
- * Monitor Output (Display Resolution)
1,920 x 1,200 (not supported by HDMI); 1,920 x 1,080; 1,360 x 768;
1,600 x 1,200; 1,280 x 1,024; 1,024 x 768
- * Display Frame Rate Max. 60 fps (30 fps x 2 channels) at 1,920 x 1,080 at 4 Mbps
Max. 60 fps (15 fps x 4 channels) at 1,920 x 1,080 at 4 Mbps
Max. 120 fps (30 fps x 4 channels) at 1,280 x 720 at 2 Mbps
Max. 135 fps (15 fps x 9 channels) at 1,280 x 720 at 2 Mbps
Max. 270 fps (30 fps x 9 channels) at 720 x 480/576 at 1 Mbps
Max. 240 fps (15 fps x 16 channels) at 720 x 480/576 at 1 Mbps
- * Monitor Output *6 HDMI (x1), analog RGB (D-sub 15-pin) (x1)
- * Audio Output 1 channel (HDMI)

Specifications

Video Interface Specifications	Detail
Monitor Output Connector	HDMI (x1), analog RGB (D-sub 15-pin) (x1)
General Specifications	Detail
Dimensions (W x H x D)	6 3/4 inches x 3 1/4 inches x 1 1/8 inches (170 mm x 80 mm x 27 mm) (exclusive projections)
Weight	HDMI (x1), analog RGB (D-sub 15-pin) (x1)
Operating Temperature	41F to 104F (5C to 40C)