

LX Hybrid Digital Video Recorder with Looping Outputs

D12LX

8 Ch. 960H Analog + 4 Ch. IP Hybrid Digital Video Recorder


D₂0LX

16 Ch. 960H Analog + 4 Ch. IP Hybrid Digital Video Recorder

Storage

1TB - 9TB

D12LX1TB D12LX6TB D20LX1TB D20LX6TB D12LX2TB D12LX9TB D20LX2TB D20LX9TB D12LX3TB D20LX3TB D12LX4TB D20LX4TB



Features

EZ Set-Up Wizards: one click wizard guides you to set up essentials of the system in a logical and easy to understand sequence.

- Date/Time Recording method Recording video quality Network
- Port forwarding

EZ Search: quickly search events from thumbnails

EZ Record: quickly setup recording resolutions and recording type

EZ Copy: auto copy what you are playing onto a USB flash drive

- 8 or 16 analog channels (960H) + 4 IP channels (1080p)
- ONVIF support*
- Video Out: 1 HDMI[®], Loop Out, 1 Spot, 1 VGA
- Multiple search engines (date/time, calendar, record table, event, motion, museum)
- · Auto port forwarding and SSL encryption
- · 2-way audio communication
- Digital Deterrent® for triggering audio message via motion detection or sensor
- · Built-in DVD RW drive
- Built-in S.M.A.R.T. Technology (Self-Monitoring, Analysis and Reporting Technology for HDD)
- Free Speco DDNS service for use with dynamic IP addresses
- MAC® & PC compatible software included
- POS/ATM support with text overlay and searchable database
- SNS communication alert via Twitter™
- · Remote monitoring, recording, playback, change system settings and dome camera control via network
- IR remote control included individually control up to 16 DVRs

- USB 2.0 port for video clip exporting
- · Configurable per channel normal and event recording frame rate and picture quality or globally via EZ Record
- · Easy software upgrade via network or USB flash drive
- Free Central Management System (Speco Central II) software allows viewing of multiple DVRs on a PC
- Concurrent User Connections: Admin (2), Watch (10), Search (2)
- · Digital zoom in live mode and playback
- · Covert camera operation provides enhanced security and administrator control
- · Playback while watching live on same monitor
- · Up to 30 minutes pre-alarm recording
- · Up to 30 minutes post-alarm recording
- USB mouse supported (not included)
- · Password to secure installation with configurable user authentication levels
- Rack mountable (hardware included)
- SecureGuard® compatible
- 3 year warranty

Free Apps with support for view on most smart devices

*Visit www.specotech.com/onvif.html for latest ONVIF support. iPhone is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. Blackberry is registered to Blackberry. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/12/14









Onvie **Hami**



	ITEM			D12LX	D20LX	
			Channel	8 analog + 4 IP	16 analog + 4 IP	
			Input Level	Composite 1.0Vp	n-p / 75 ohms	
Video	Input		Signal Format	NTSC /	PAL	
			Video Loss Check	Yes		
	Output		HDMI®	1 HDMI (1280x1024 / 1440x900 / 1920x1080)		
			VGA			
				1 VGA (1280x1024 / 1440x900 / 1920x1080)		
			BNC Spot	1 channel se	·	
			Loopout	8 analog	16 analog	
	Input			4 line		
Audio	Output			1 line		
	Audio Codec			G.711		
Alarm	Serial Input (NC/NO Selectable)			8	16	
	Alarm Output			2 alarm out by sensor, motion and video loss		
	RS-232 POS		POS	1		
	RS-485		PTZ/POS	1		
	Compression			H.264		
	Multi-Operation		n	Quadplex (play, record, network, backup)		
Recording			960H	240fps	288fps	
	Ar	nalog	D1	240fps	480fps	
	Resolution		CIF	480fps	480fps	
	1 Coolullol1		720p	120fp	· · · · · · · · · · · · · · · · · · ·	
		IP -	-			
	1080p		·	70fps Cont / Schedule / Motion / Sensor / Panic		
	Recording Mode			-		
	Motion Detection			Motion detection grid		
	Recording by Channel's Resolution			Yes		
	Pre-Recording			5 seconds to 30 minutes before an event		
	Post Recording			5 seconds to 30 minutes after an event		
Playback	Multi-Decoding			1, 4, 6, 9, 12, PIP	1, 4, 6, 9, 12, 16, 20, PIP	
1 layback	Search Mode		;	Date/Time, Record Table, Calendar, Event, Motion, Museum, Text-In, EZ Search		
	HDD Backup		Interface Type	SATA 2.0		
Storage			Capacity of 1 HDD	3TB	3TB	
			Internal HDD Number	3		
			USB Flash Drive	Video & Stil	I Image	
			USB External HDD	Video & Stil	Video & Still Image	
			Network	Video & Still Image		
	USB Port			2 front		
	Interface			10/100/1000Base-TX Ethernet		
Network	Streaming			CIF120fps (analog) / depends on profile (IP)		
	IP Camera Throughput			24 Mbps		
	Mobile Viewer			Speco Mobile (Live, Search, PTZ, 2-Way Audio)		
etwork Access	PC Web Viewer		51	Internet Explorer (Live, Search, Backup, PTZ, Remote Setup)		
	PC Client			Speco Central II and SecureGuard® (Live, Search, Backup, PTZ, Remote Setup)		
	MAC Client			Speco Remote for MAC and SecureGuard® (Live, PTZ)		
		Deterrer		Default + up to 16 custom audio files		
	Digital Zoom			Live: x2, x3, x4 / PI	-	
	DLS (Daylight Savings)			Yes		
	EZ Record			Yes		
	S.M.A.R.T			Yes		
	Internal Beep			Yes		
Features	Multi-Language			English, French, Spanish		
Features	Multi-L			Yes (free Speco DDNS)		
Features		mic DNS	8		co DDNS)	
Features	Dyna	mic DNS Upgrade		USB and remote so	· · · · · · · · · · · · · · · · · · ·	
Features	Dyna SW U				ftware upgrade	
Features	Dynai SW U Email N	Upgrade Notificati	on	USB and remote so	ftware upgrade	
	Dynai SW U Email N NTP (Networ	Upgrade Notification	on Protocol)	USB and remote so Yes Yes	iftware upgrade	
Power Source	Dynai SW U Email N NTP (Networ Power Su	Upgrade Notification rk Time Fupply Vol	on Protocol)	USB and remote so Yes Yes 12VDC,	ftware upgrade	
Power Source	Dynai SW U Email N NTP (Networ Power Su wable Operating Temperature	Upgrade Notification rk Time Fupply Vol	on Protocol)	USB and remote so Yes Yes 12VDC, 41° F - 104° F / 0	ftware upgrade 5A % – 90% RH	
Power Source	Dynai SW U Email N NTP (Networ Power Su	Upgrade Notification rk Time Fupply Vol r / Humid ature	on Protocol) Itage	USB and remote so Yes Yes 12VDC,	5A 1% – 90% RH 22° F	

Please note that specifications and unit exterior design are subject to change without notification.