

Intensifier3® Series Miniature Weather/Vandal/Tamper Resistant Dome Camera with Chameleon Cover™


See Color In Almost Complete Darkness Without IR LEDs

HINT13D7G 3.6mm fixed lens, dark grey housing

**INT
3**



Shown with included paintable, snap-on Chameleon Cover™



Features

- 1/3" Sony Super HAD™ CCD
- 650 TV lines of color resolution
- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- Minimum illumination 0.00002 lux (Intensifier3® @ 512x)
- Chameleon Cover™: snaps on and can be painted to match any décor!*
- Full OSD operation
- Now with Presets: Outdoor, Indoor, Elevator, Hallway & Dark
- Wall or ceiling mount
- 12VDC / 24VAC dual voltage operation
- Vandal resistant operation: can withstand hits from a 10 lb. sledgehammer!
- Tamper resistant operation: tamperproof screws for enhanced security
- Weather resistant operation: good for indoor or outdoor usage
- IP66 compliant
- 5 year warranty

Specifications

Image Sensor.....	1/3" Sony Super HAD™ CCD	AGC.....	High / Middle / Low / Off
Resolution.....	650 TV lines	White Balance	ATW1 / ATW2 / ATW set / Manual
Minimum Illumination.....	Shutter: 0.03 lux Intensifier3®: 0.00002 lux	Intensifier3®.....	Auto / Off (selectable x2 - x512)
Effective Pixels	768 (H) x 494 (V)	Motion Detection.....	On / Off (8 programmable zones)
Total Pixels	811 (H) x 508 (V)	Privacy Masking	On / Off (8 programmable zones)
Scanning Frequency.....	15.734kHz (H) & 59.94Hz (V)	Speco DNR.....	On / Off (level adjustable)
Scanning System.....	2:1 interlace	Digital Zoom	On / Off (1x - 8x)
Synchronization.....	Internal	DIS.....	On / Off
S/N Ratio	More than 52dB	Sharpness	On / Off (level adjustable)
Video Output.....	CVBS: 1.0Vp-p / 75 ohms	Flip / Mirror	On / Off
Electronic Shutter Speed.....	Auto / AFLK (1/60 sec. - 1/90,000 sec.)	Power Supply	12VDC / 24VAC dual voltage operation (power supply not included)
OSD.....	Available	Power Consumption	12VDC, 130mA / 24VAC, 75mA
WDR.....	On / Off (level adjustable)	Operating Temperature.....	-20° F – 122° F
Backlight Compensation.....	BLC / HLC / Off	Dimensions.....	3.07" (H) x 4.33" (Dia.)
Day/Night.....	Color / BW / Auto	Weight	1.54 lbs.

*Chameleon Cover™ - for best results when used outdoors, waterproof paint is recommended. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 5/28/13



Optional Accessories



PSW4
24VAC
Power Supply



PSW5
12VDC
Power Supply