


960H Indoor/Outdoor IR Dome Camera with 10x Optical Motorized Zoom

HTD10XH 3.8-38mm auto iris varifocal lens (10x optical zoom), dark grey housing



Shown with included paintable, snap-on Chameleon Cover™



Features

- 1/3" Sony ExView™ CCD
- 700 TV lines of resolution
- 28 IR LEDs
- Highest resolution: vivid sharp picture in complete darkness
- Motorized zoom lens control via RS485
- Chameleon Cover™: snaps on and can be painted to match any décor!*
- 3DNR (digital noise reduction)
- DWDR (digital wide dynamic range)
- Smart digital zoom
- Full OSD operation
- Digital image stabilizer
- 3 axis lens mount
- IP67 compliant
- 12VDC / 24VAC dual voltage operation
- 5 year warranty

Specifications

Image Sensor	1/3" Sony ExView™ CCD
Resolution.....	700 TV lines
Minimum Illumination.....	0 lux
Effective Pixels	976 (H) x 494 (V)
Total Pixels	1028 (H) x 508 (V)
TV System.....	NTSC
Scanning System.....	2:1 interlace
Number of IR LEDs	28
IR Range	98 ft. (depending on scene reflection)
IR LED Wavelength	850nm
S/N Ratio	52dB
Video Output.....	1.0Vp-p / 75 ohms
Backlight Compensation.....	On / Off
Day/Night.....	Auto / Color / BW / Ext
AGC.....	High / Middle / Low
Sense-Up.....	Auto / Off (x2 – x256)
White Balance	ATW / AWB / AWC – Set / Manual (1,800°K – 10,500°K)

Mirror	H-Rev / V-Rev / Rotate / PIP
Digital Zoom	x12
Defect Compensation.....	Auto (256 points)
3DNR.....	On / Off / Smart
DIS.....	On / Off
Power Supply	12VDC / 24VAC dual voltage operation (power supply not included)
Power Consumption	12VDC, 700mA / 24VAC, 350mA
Storage Temperature/	
Humidity.....	-4° F – 140° F / 20% – 95% RH
Operating Temperature/	
Humidity.....	-4° F – 140° F / 20% – 80% RH
Dimensions.....	5.12" (Dia.) x 3.94" (H)
Weight	1.98 lbs.

Optional Accessories



INTPM
Pendant Mount



INTWM
Wall Mount



DFM
Tile Ceiling Flush Mount



INTCM
Corner/Pole Adaptor
(use with INTWM)




CVCJBD
Dome Camera Junction Box



PSW4
24VAC Power Supply



PSW5
12VDC Power Supply

 * Chameleon Cover™ - for best results when used outdoors, waterproof paint is recommended. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 1/20/14