



4.3" IP/HD Analog Tester

- Touch Screen & Built In Wifi
- Easily Detect IP Addresses
- Supports ONVIF + ONVIF PTZ
- Recording + Storage to SD Card
- Video Playback/Snapshot
- CVI, TVI, SDI, AHD, CVBS

Built-In Lithium Polymer Battery
5000mAH
6 Hr Charging Time
5 Hr Continuous Operating Time

Built- In Kick Stand
Carrying Bag also included



Specifications subject to change without notice



Western Regional Sales 562-295-2812 jiozzi@tatungusa.com
Eastern Regional Sales 562-295-2811 myu@tatungusa.com
www.tatungusa.com

4.3" IP/HD Analog Tester

Specifications

Display	4.3 capacitive OLED touchscreen
Resolution	800 x 480
Supported IP Cameras	ONVIF & ONVIF PTZ
SDI	1 channel SDI input (BNC Interface)
CVI	1 channel CVI input (BNC interface)
TVI	1 channel TVI input (BNC interface)
AHD	1 channel AHD input (BNC interface)
Analog Video	1 channel BNC & 1 channel BNC output
Audio	1 channel single input, 1 channel audio signal output to connect headphones
PoE Power Output	48V PoE power output, Max power 24W
12V/2A Power Output	Output DC12V/2A power for camera
USB 5V Power Out	5V 2A power output only, no data
External Power Supply	DC 12V (2A)
Battery	Built in 7.4V Lithium Polymer battery, 5000mAh
Dimensions	Weight 8.36" x 5" x 2.07"
Weight	1.86 lbs

Specifications subject to change without notice. REVD0C#0419.17



Western Regional Sales 562-295-2812 jiozzi@tatungusa.com
 Eastern Regional Sales 562-295-2811 myu@tatungusa.com
www.tatungusa.com