



## TLM-0801 Dual Rack Mountable CCTV LED Monitor Specifications:

MODEL		TLM-0801
DESCRIPTION		
LCD Panel	Screen Size	8.0 inch diagonal
	Viewable size	162.0mm (H) x 121.5mm(V)
	Dot Pitch	0.2025mm x 0.2025mm
	View angle H/V	-70°, +70°/-70°, +60°
	Contrast ratio	500:1
	Brightness	250 cd/m <sup>2</sup>
	Resolution	800 x 600
	Response Time	≤50ms
	Display Color	262K
	Back Light Type	LED back light
Control key define		Channel, -, +, Menu, Power
Power Supply	Input-Voltage	12V <sub>DC</sub>
	Consumption	7W max.
Video	Input	Composite video, connector: 2 BNC S-video, connector: 1 mini-din 4 pin Level: 1.0Vp-p / 75Ω
	Output	2 BNC connector for CVBS loop-through output,
	OSD	Contrast, Brightness, Display Adjust, Color Temperature, Language, OSD setting, Aspect Ratio, Audio Control, Input Select, Reset, Exit
	System Compatibility	Scanning Frequency NTSC : 15750Hz ± 500Hz / 60Hz, PAL : 15625Hz ± 500Hz / 50Hz
Analog VGA	Input	Analog RGB: 0.707Vp-p / 75Ω, connector: D-sub 15pins
	OSD	Contrast, Brightness, Display Adjust, Color Temperature, Language, OSD setting, Audio Control, Input Select, Reset, Exit
	Plug & Play	EDID
	Power Management	VESA DPMS
	Support timing	VESA VGA / SVGA
Audio	Input/Output	connector: 1 x RCA input/ 1 x RCA output Level: 1.0Vp-p / 1 KHz
	Speaker	1W x 1 embedded
Mechanical	Dimension	202x175.8x29.2mm <sup>3</sup>
	Weight	2.6lbs (1.17Kg)
Additional benefit		FCC, CE certified Wall mount pattern 40x40mm <sup>2</sup> Optional Dual Rack Mount Kit TRK-0801 RoHS compliant

Note: The specifications are subject to change without notice.

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com



**AUDIOVIDEO SUPPLY**  
1-800-284-2288 sales@avsupply.com  
www.avsupply.com

For design help, accessories or pricing, please contact:  
sales@avsupply or call: 1-858-565-1101