

The logo for TRIVIEW, featuring three red slanted bars to the left of the word "TRIVIEW" in a bold, black, sans-serif font.

Universal IP Camera Test Monitor



- 4.3" OLED Touch-Screen Display
- Multiple IP Camera Protocols
- MicroSD Card Slot (Supports Up To 32GB)
- Sunlight Readable
- Tests for Wire Pin Alignment
- USB 2.0 Upgrade FW + Google Apps
- 3 Year Warranty

TOM-0431IP is an IP installation and service tool that works with a variety of the most popular IP camera protocols. The TOM-0431IP is highly portable and includes a 4.3" sunlight viewable touch-screen display in wide-screen format. The unit incorporates POE function as well as a "snapshot" function. A Leather carrying case along with a velcro wrist strap is included for hands-free operation. The battery powered TOM-0431IP includes a cable for charging the unit's internal battery. In addition to IP connection, the TOM-0431IP also includes a BNC input and output for use with analog cameras.



INCLUDES:
VELCRO WRIST STRAP
LEATHER CASE
CARRYING BAG

*Visit www.tatungusa.com For Camera Protocols. Protocols list will be updated periodically. Specifications are subject to change without notice

TRIVIEW is a trademark of Tatung Company of America, Inc. 1-800-829-2850

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101

AUDIOVIDEO SUPPLY
1-800-284-2288 sales@avsupply.com
www.avsupply.com

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

TOM-0431IP

4.3" OLED Test Monitor

- Multi-Touch Screen
- Sunlight Readable
- Rechargeable
- IP or Analog
- POE and SnapShot Function
- Micro SD Card Slot



Screen Size	4.3" Diagonal
Technology	OLED
Aspect Ratio	16:9
View Angle H/V	-80°, +80°/-80°, +80°
Contrast Ratio	10,000:1
Brightness	250 cd/m ²
Resolution	480 x 272
Response Time	2ms
Display Color	16.7M
Input Voltage	12VDC / 3.0A
Consumption	<6.5W
Charger	Input: 100~240VAC, 1.3A, 50-60Hz, Output: 12VDC/3.0A
Battery	7.2VDC/2600mAH 2-Cell Li-ion Battery (Embedded Inside The Device)
Memory	MicroSD Slot (Supports MicroSD Memory Card Up To 32GB) Memory Card Is Not Included 1GB Internal Memory
Input	Composite Video, Connector: 1 BNC Level: 1.0Vp-p / 75Ω 2 RJ45; LAN IN and PoE/Power Bank IN
Output	1 BNC Connector for CVBS Loop-Through and Test Pattern Output 1 RJ45; CAT-5 Cable Tester
Video Support	NTSC and PAL
Charging Time	3.5 Hours Average
Operating Time	Continuous Display Time: 3-Hours Average (2-Hours PoE ON) Standby Time: 6+ Hours
Operating Temperature	32° F-104° F
Dimensions	5.6" x 1.06" x 3.74"
Weight	Net: 12oz / Gross: 3lbs 4oz



Specifications subject to change without notice. Rev#0313.14

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com