

High-Density Storage for Enterprise Networks

Toshiba NVSPRO servers are designed for high-performance, large storage applications. With capacities up to 24TB and 48TB, Intel Core i7 processors, and dual Gigabit Ethernet ports, the NVSPRO is capable of handling demanding high-megapixel, enterprise-class deployments. Available in either 2U or 4U rackmount chassis, the NVSPRO offers superior performance and high storage density in space-saving form factors.

- 8 or 16 removable hard drives for storage up to 24TB or 48TB
- Intel Core i7 Processor
- Dual Gigabit Ethernet ports
- Includes 8 IP licenses expandable to 64

- 2U or 4U rackmount sizes
- Supports over 150 IP camera models
- Free Surveillix VMS software
- RAID5 option available







NVSPRO High Performance Network Video Servers

TOSHIBA Leading Innovation >>>

SERIES OVERVIEW			PART NUMBERS
Image compression	H.264, MPEG4, MJPEG		NVSPRO8-2U-2T
Max Number of Channels	8 included, Expandable up to 64 (data rate dependent)		NVSPRO8-2U-4T
Video Outputs	HDMI x 1, DVI x 1 (simultaneous output)		NVSPRO8-2U-8T
Audio 1 a	audio jack input, Up to 64 IP camera audio input, 1 audio out		NVSPRO8-2U-12T
STORAGE			NVSPRO8-2U-15T
Storage Capacity	Up to 24TB (2U) Up to 48TB (4U)		NVSPRO8-2U-18T
Critical Recording Archive	DVD/RW, eSATA x 1		- NVSPRO8-2U-21T
FRAME RATES			NVSPRO8-2U-24T NVSPRO8-4U-30T
Throughput	Up to 90 Mbs (non-RAID5 configuration)		NVSPR08-40-301 NVSPR08-4U-36T
	Up to 260 Mbps (RAID	05 configuration)	NVSPR08-4U-42T
INPUTS/OUTPUTS			NVSPR08-4U-48T
PTZ Controls Protocols	Supported Network	< Cameras ¹	
LAN	2 x 100/1000 Gigabit Ethernet		RAID5 PART NUMBERS
USB	8 x USB2.0, 2 x USB3.0		RAID5-2TA
OTHER			RAID5-4TA
Remote Connection	TCP/IP, UDP, Internet, LAN, WAN		RAID5-8TA
Password Control	User defined access level		RAID5-12TA
Power Interruption Recovery	y Automatic restart and resume		RAID5-15TA
SYSTEM			RAID5-18TA
CPU	Intel Core i7		RAID5-21TA
RAM	4GB		- RAID5-24TA
Operating System	Windows 7 Embedded		RAID5-30TA
DIMENSIONS			RAID5-36TA RAID5-42TA
Dimensions (h x w x d)	3.5" x 17.25" x 26.25" (2U)	6.9" x 16.95" x 26.25" (4U)	RAID5-42TA RAID5-48TA
Weight	48 lbs w/o HDD	59 lbs w/o HDD	
POWER			
Power Input	AC 100-240V (50Hz/60Hz) ²		
Power Consumption	340 watts typical		
INCLUDED ACCESSORIES			
Accessories	Rackmount ears, keyboard and mouse		
WARRANTY			
Limited Warranty	3 years, 1 year advance replacement		

1. For supported device list, visit our Integration page: www.toshibasecurity.com/integration

2. 2U chassis cannot have a redundant power supply.



2U Chassis

©2012 Toshiba America Information Systems, Inc. All rights reserved. All products and names mentioned are the property of their respective owners. While Toshiba has made every effort at the time of publication to ensure the accuracy of the information provided herein, product specifications, configurations, prices, system/component/options availability are all subject to change without notice.



4U Chassis

Toshiba America Information Systems, Inc. Surveillance & IP Video Products, Imaging Systems Division 9740 Irvine Boulevard, Irvine, California 92618 1-877-855-1349 • www.toshibasecurity.com