



LED-1003HD

This 9.7" LED-backlit monitor features the latest screen imaging technology for enhanced clarity and sharpness. Both analog and digital video will benefit by being viewed on this monitor, and it is the best match for displaying higher resolution megapixel imagery.

Benefits

- LED backlight for better color, longer-life, and lower power
- Wide viewing angle
- Excellent contrast ratio
- Very fast response time
- Image enhancing - 3D Interlace comb filter, DNR, 4H filter
- Durable metal case

Accessories

- DC-1500 Factory approved car cord
- HM-401 Under-cabinet hinge mount
- WM-31 Wall mount bracket (fixed)
- WM-302 Wall mount with swing arm & 4-way adjustable

Related products

LED-1002HD2 - Dual 9.7" monitors in a rack mount

| Specifications | |
|---------------------------|---|
| Mount | VESA 75x75mm and 100x100mm, 1/4-20 pad on top, removable desk stand |
| HD Compatible | Yes |
| Anti Glare Coating | Yes |
| Case | Metal |
| Native Aspect Ratio | 4:3 |
| Visible Screen Size (WH) | 7.8" x 5.9" / 197.6 x 148.8mm |
| Resolution | 1024(H) x 768(V) |
| Brightness Rating | 400 cd/m ² (Nit) |
| Contrast Ratio | 1000:1 |
| Back Light | LED (30K) |
| PC Compatibility | Yes |
| Dot Pitch | 0.192 (H) x 0.192 (V)mm |
| Color Depth | 262,144 |
| Number of Pixels | 786,432 |
| Response Time | 2ms/2ms (Rising/Falling) |
| Audio Power / Speakers | 2 x 2 watts |
| Viewing Angle (L/R/T/B) | 89/89/89/89 degrees |
| Digital Signal Processing | 3D Interlace comb DNR, 4H filter |
| Dimensions w/o desk stand | 8.8" x 7.8" x 1.9" / 223.5 x 198 x 48.3mm |
| Operating Temp/Humidity | 32 ~ 104°F / 0 ~ 40°C |
| Power Requirements | 12VDC, 2A, negative ground |
| Power Consumption | 30 watts (Max) |
| Composite | x2 BNC Inputs; x2 BNC Outputs |
| PC | x1 15-pin mini D-sub |
| HDMI | x1 Input |
| Audio | x1 RCA L/R Input; x1 PC 3.5mm Input |
| Power | x1 2.1mm DC Input |
| Weight | Net: 2.55 lbs / 1.2 kg; Gross: 4.6 lbs / 2.1 kg |

Specifications subject to change.