



## LED-1003HDL

This 9.7" flush mount monitor features the latest screen imaging technology for enhanced clarity and sharpness. Both analog and digital video will benefit by being viewed on this monitor, and it is the best match for displaying higher resolution megapixel imagery.

### Benefits

- LED backlight for better color, longer-life, and lower power
- Wide viewing angle
- Excellent contrast ratio
- Very fast response time
- Image enhancing: 3D Interlace comb filter, DNR, 4H filter
- Durable metal case

### Related products

LED-1002HDLX: 9.7" flush-mount monitor with no front controls  
LED-1002HDL: 9.7" flush-mount monitor with RS-232 and Gorilla Glass

### Installer's Cutout

8 7/8" x 7 3/4" / 223 x 196.4mm

### Specifications

Mount	Flush Mount
HD Compatible	Yes
Anti Glare Coating	Yes
Selectable Color Temp.	Yes
Case	Metal
Native Aspect Ratio	4:3
Visible Screen Size (WH)	7.8" x 5.9" / 197.6 x 148.8mm
Resolution	1024(H) x 768(V)
Brightness Rating	400 cd/m <sup>2</sup> (Nit)
Contrast Ratio	1000:1
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.192 (H) x 0.192 (V)mm
Color Depth	262,144
Number of Pixels	786,432
Response Time	2ms/2ms (Rising/Falling)
Audio Power / Speakers	x2 Speakers
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Pixel Configuration	RGB Vertical Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
Digital Signal Processing	3D Interlace & DNR, 4H filter
Dimensions	10.75" x 9.75" x 1.85" / 273 x 247.7 x 47mm
Operating Temp/Humidity	32 ~ 104°F / 0 ~ 40°C
Power Requirements	12VDC, 2A, negative ground
Power Consumption	30 watts (Max)
Composite	x2 BNC Inputs; x2 BNC Outputs
PC	x1 15-pin D-sub Input
HDMI	x1 Input
Audio	x1 RCA L/R Input, PC 3.5mm Input
Power	2.1mm DC Input
Weight	4 lbs. net , 6.25lbs. gross

Specifications subject to change.