



LED-1906HDT

High-definition, LED-backlit, mid-size monitor that is versatile and effective for any commercial video use.

Benefits

- Displays HD signals (1080i/p and 720p)
- 3D + 3D image processing with digital noise reduction
- Built-in ATSC / Clear QAM Tuner
- Durable ABS Plastic Housing
- Built-in speakers
- Built-in removable desk stand
- 75mm VESA pattern for mounting
- IR remote control

Related Products

- LCD-1906HDTL: Flush mount version
- LCD-1906HDTR: Rack mount version

Accessories

- HM-401 Under-cabinet hinge mount
- WM-31 Wall mount bracket (fixed)
- WM-302 Wall mount with swing arm & 4-way adjustable
- WMC-2346 Ceiling mount bracket for 1.5" NPT pipe



Specifications

Mount	Desk Stand: VESA 75 x 75mm
Screen Panel	18.5" TFT Active Matrix
HD Compatible	Yes
Anti Glare Coating	Yes
V Chip/Closed Caption	Yes
Case	Durable ABS Plastic
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	409.8 x 230.4mm / 16.1" x 9.1"
Resolution	1366(H) x 768(V)
Brightness Rating	230 cd/m ² (Nit)
Contrast Ratio	1000:1
Back Light	LED
Dot Pitch	0.30(H) x 0.30(V)mm
Color Depth	16.7M
Number of Pixels	1,049,088
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	8 ohm, 2 x 2 watts
Viewing Angle (L/R/T/B)	85/85/80/80
3D Comb Filter	Yes
Removable Desk Stand	Yes
Dimensions w/o Deskstand	469 x 362 x 36mm/18.5" x 14.25" x 1.4"
Operating Temp/Humidity	6 ~ 104°F / -14 ~ 40°C
Power Requirements	100 ~ 240 VAC, 50/60Hz
Power Consumption	<25 watts; <= 0.5 watts (standby)
Component	x1 RCA y/Pb/Pr Input
Composite	x2 RCA Inputs; x1 RCA Output
VGA (RGB)	x1 15-pin mini D-sub Input
HDMI	x3 Input
TV (RF)	x1 F (Coax) Input
Audio	x1 RCA L/R Output, 3.5mm earphone Output
Weight	Net 4 kg / 8.8 lbs., Gross 5 kg / 11 lbs.

Specifications subject to change.