



## LED-3206HDT

Aesthetically-designed, commercial-grade, LED-backlit LCD monitor with ATSC / Clear QAM tuner provides exceptional picture quality using the latest DSP technology. This monitor is ideal for use in any commercial AV application.

### Features

FHD display (1080i/p) with high contrast ratio and 3D comb filter digital signal processing for better picture definition

Wide viewing angle

### Related Products

LED-5000HDT: 50" LCD monitor with ATSC/Clear QAM tuner

LED-4203HDT: 42" LCD monitor with ATSC/Clear QAM tuner

### Accessories

WM-302: 4-way VESA wall mount with swing-arm; supports up to 22 lbs

WM-3742VT: Heavy duty dual-arm wall mount; supports up to 150 lbs

### Specifications

Mount	VESA 100 x 100mm wall-mount; Desk stand
Anti Glare Coating	Yes
Case	Durable ABS Plastic
IR Remote Control	Infrared
Native Aspect Ratio	16:9
Visible Screen Size (WH)	27.6" x 15.5" / 702 x 394mm
Native Resolution	FHD: 1920(H) x 1080(V); displays 1080i/p
Brightness Rating	280 cd/m <sup>2</sup>
Contrast Ratio	1,200:1
3D Comb Filter	Yes
Back Light	LED (30K)
Color Depth	16.7 Million
Number of Pixels	2,073,600
Response Time	8ms (rising / falling)
Viewing Angle (L/R/T/B)	88/88/88/88 degrees
Tuner	ATSC / Clear QAM (F Connector)
Component Video	x1 RCA YPbPr (3 Inputs)
Composite Video	x2 RCA Inputs; x1 RCA Output
HDMI	x3 Inputs
VGA	x1 RGB 15-pin D-sub
Audio Ports	x2 3.5mm Audio Input; x1 RCA L/R Audio Output x1 3.5mm Earphone Input
Audio Power	8 watts x2 Speakers
USB	x2 Inputs
Operating Temp/Humidity	41 ~ 104°F / 5 ~ 40°C; 10% ~ 85% humidity
Power	x1 AC Input
Power Requirements	100 ~ 240 VAC, 50/60 Hz
Power Consumption	55 watts (Max); 5 watts (Standby)
Dimensions (without Desk stand)	29.1" x 19.4" x 2.7" / 739 x 492 x 68mm
Weight	Net: 15.4 lbs / 7 kg; Gross: 19.8 lbs / 9 kg

Specifications are subject to change.