

LED-430X4-3GSDI - Front



LED-430X4-3GSDI - Back



LED-430X4-3GSDI

Functional and beautiful, this new generation model includes four LED-backlit, LCD monitors in a rack mount configuration. Each 4" monitor includes a native 3G-SDI input signal that is SMPTE 424M compliant, handling bit-rates of 2.97Gbit/sec which supports 1080p video up to 60 frames per second. This model is an ideal solution for broadcast studio environments that distribute and monitor VOD 1080p streams.

Benefits

- 3G/HD/SD-SDI Input and Output
- Quick access source buttons
- Wide viewing angle
- Up/Down tilting
- Tally function

Related Products

LED-500X3-3GSDI

Specifications	
Model	LED-430X4-3GSDI
Mount	Rack: 3 RU
HD Compatible	yes
Case	Durable metal
Native Aspect Ratio	16:9
Visible Screen Size (WH)	93 x 55.8mm /3.7" x 2.2"
Resolution	800 x 480 dots
Brightness Rating	200 cd/m ² (Nit)
Contrast Ratio	400:1
Back Light	LED (15 K)
Dot Pitch	0.116(H) x 0.116(V)
Colors	16.7M
Response Time	20msec
Viewing Angle (L/R/T/B)	65/65/45/65
Dimensions	19" x 5.25" x 6.9" (3 RU)
Operating Temp/Humidity	32 ~ 185°F or 0 ~ 85°C, 85% RH max.
Power Requirements	12VDC, 5A
Power Consumption	45W (max)
Component	[BNC x 3] x 4
Composite	BNC Video IN x 4
S-Video	mini-DIN x 4
PC	D-sub (15 pin) x 4
HDMI	yes
Tally Input	D-sub (9 pin)
Audio	No
Power	screw in DC jack
Weight	Net 5.5 kg / 12.1 lbs, Gross 6.7 kg / 14.75 lbs