



LED-803HD

This adaptable small screen monitor is ideal for use in security surveillance and professional AV environments where space can be limited and constant use is often required.

Benefits

- Anti-glare coating provides enhanced display
- Durable metal case
- Remote control for maximum proficiency
- PC Connectivity
- Built-in Speakers
- Always-on capability when power is applied

Accessories

- DC-1500 Factory approved car cord
- HM-401 Under-cabinet hinge mount
- WM-31 Wall mount bracket (fixed)
- WM-302 Wall mount with 4-way adjustable swing arm

Related Product

LED-803HD2

Specifications

| | |
|--------------------------|---|
| Mount | VESA: 75 x 75mm; removable deskstand; 1/4 - 20 pad top/bottom |
| Anti Glare Coating | Yes |
| Case | Metal |
| IR Remote Control | Yes |
| Native Aspect Ratio | 4:3 |
| Visible Screen Size (WH) | 6.4" x 4.8" / 162.0 x 121.5mm |
| Resolution | 800(H) x 600(V) |
| Brightness Rating | 250 cd/m ² (Nit) |
| Contrast Ratio | 500:1 |
| Back Light | LED (20K) |
| Dot Pitch | 0.0675(H) x 0.2025(V)mm |
| Color Depth | 16.7M |
| Number of Pixels | 480,000 |
| Response Time | 25ms (Rising/Falling) |
| Audio / Speakers | 1.5W x 2 speakers |
| Viewing Angle (L/R/T/B) | 70/70/50/70 |
| Pixel Configuration | RGB Vertical Stripe |
| Dimensions w/ Deskstand | 8.8" x 6.9" x 2.6" / 223 x 176.2 x 66.2mm |
| Dimensions w/o Deskstand | 8.8" x 6.9" x 1.9" / 223 x 176.2 x 47mm |
| Operating Temp | 32 ~ 122°F / 0 ~ 50°C |
| Humidity | 10% ~ 90% |
| Power Requirements | 11.5~13 VDC, 1.2A |
| Power Consumption | 10 Watts |
| Composite | x2 BNC Inputs; x2 BNC Outputs |
| PC | x1 15-pin D-sub |
| Audio | x2 R/L (RCA) Inputs; x1 3.5mm PC Input |
| Power | 2.1mm DC Input |
| Weight | Net 2.9 lbs / 1.3 kg |

Specifications subject to change