



SDP12/16 SuperDome™ Housing

The SuperDome is a general purpose dome camera housing. This unit is available with either a 12" or 16" dome and comes with a pendant mount. It features a ¼" UV rated, ABS plastic upper dome and a 1/8" cell-cast acrylic lower dome. The 12" model allows two fixed cameras, the 16" unit allows for three cameras.

Features

- Available with clear or tinted dome
- Optional inner liner available
- Security fasteners standard equipment
- Houses single or multiple fixed cameras
- Optional heater / blower



SDP12/16

Outdoor/ Indoor SDP12:

SDP12C

12" outdoor / indoor fixed camera dome housing. Includes 1 fixed camera bracket; can accommodate up to 2 full-body fixed cameras (FM1). Security fasteners, optional pendant mount, MCL (Maximum Camera Length) 7"-8"

SDP12CHB

12" outdoor / indoor fixed camera dome housing. Includes 1 fixed camera bracket; can accommodate up to 2 full-body fixed cameras (FM1). Security fasteners, optional pendant mount, heater / blower (included in outdoor models), MCL 7"-8"


Moog specializes in housings for fixed, multi-camera applications. These configurations offer an inexpensive alternative to pan / tilts. The SuperDome™ offers:

- Ability to accommodate up to 3 fixed cameras:
SDP12 MCL: 8" for 1 camera / 7" for 2 cameras
SDP16 MCL: 12" for 1 camera / 8" for 2 cameras / 7" for 3 cameras
- Adjustable viewing in many directions • Easy Installation

NOTE: If the application calls for more than one camera in the unit, an additional FM1 bracket will be needed for each additional camera

Electrical Specifications	
Power Source:	24Vac
Power Consumption:	52vA (camera not included)
Pan / Tilt Power Consumption:	16 vA (max) - .625 Amps P/T
Maximum Load:	5 Lbs. balanced
Weight:	3.25 Lbs. (1.47 Kg.)

Dimensions / Architectural Drawings				
SDP12:	A	12.0"	B	15.25"



Outdoor/ Indoor SDP16:

SDP16C

16" outdoor / indoor fixed camera dome housing. Includes 1 fixed camera bracket; can accommodate up to 2 full-body fixed cameras (FM1). Security fasteners, optional pendant mount, MCL 10"

SDP16CHB

16" outdoor / indoor fixed camera dome housing. Includes 1 fixed camera bracket; can accommodate up to 2 full-body fixed cameras (FM1). Security fasteners, optional pendant mount, heater / blower (included in outdoor models), MCL 10"

Accessory:

WM20G


Aluminum gooseneck wall bracket

- Durable powder coat finish
- All aluminum construction
- 1½" pipe thread on end for quick and easy dome mounting



Engineering Specifications	
Each unit in the SuperDome™ general purpose, outdoor housing series shall be equipped with a pre-attached, optional pendant mount, and shall be available with either a 12" or 16" clear or tinted (1 F-stop light reduction) lower dome made from 1/8" cell-cast acrylic. The upper dome shall be ¼" ABS plastic. Optional items shall include: 24Vac, 2.08 Amp heater and surge protector; 24Vac, 16 Amp blower and surge protector, or heater / blower combination; 355 integral pre-wired 12° per second.	

Dimensions / Architectural Drawings				
SDP16:	A	16.0"	B	18.4"



MOOG

Sensor and Surveillance Systems

3650 Woodhead Drive Northbrook, IL, USA 60062

+1.847.498.0700 Fax: +1.847.498.1258 www.moogS3.com