



## Warrior 6

### Discrete Vandal Resistant Camera System

The Warrior 6 (WS6) offers an inconspicuous solution to video surveillance. The discrete and rugged vandal-resistant body of the WS6 is ideal for monitoring high risk areas in a compact and durable package. A 12-gauge steel front cover and polycarbonate window with scratch resistant coating protect camera equipment, while the 16-gauge steel back box conveniently allows wiring access through the top, side or bottom. The environmentally sealed front cover is secured with tamper-resistant fasteners. The Warrior 6 comes with a high resolution Day and Night color camera. The front cover is available in off-white or stainless steel powdercoat finishes. The stainless steel finish presents the WS6 in a more sophisticated light for environments, such as office lobbies, elevators and hotels. The sturdy construction and small size make it perfect in applications such as hospitals, schools, government buildings, and correctional facilities.

#### Features

- Compact design
- High resolution Day & Night color camera, with 3.6mm fixed lens
- 12-gauge steel white front plate, optional stainless steel
- 16-gauge steel back box
- Adjustable camera bracket, allowing tilt
- Tough, 1/8" polycarbonate viewing window
- Conduit knockouts in the top, side, and bottom
- Vandal-proof paint shield (patent pending)



# Warrior 6

## Corner Mount Housing:

### WS6

Designed for indoor applications, the Warrior 6 offers discreet surveillance in a compact package. A 12-gauge steel front cover and polycarbonate window with a scratch resistant coating protect camera equipment, while the 16-gauge steel back box allows wiring access through the top, side or bottom. The Warrior 6 comes complete with a choice of cameras. The sturdy construction and small size make it perfect in applications such as hospitals, schools, government buildings, and correctional facilities.

### WS6-50NF

Warrior 6 Vandal Resistant Indoor corner mount camera, high resolution Day and Night Camera with 3.6mm fixed lens. Powdercoated white face plate

### WS6S-50NF

Warrior 6 Vandal Resistant Indoor corner mount camera, high resolution Day and Night Camera with 3.6mm fixed lens. Stainless steel face plate

### WS6-50NF-X2

WS6-50NF plus twisted pair

### WS6S-50NF-X2

WS6S-50NF plus twisted pair

## General Specifications

Environmental:	Indoors
Mounting Style:	Corner mount
Product Dimensions:	3.1" x 6.5" x 6.0" (77 x 165 x 127mm)
Product Weight:	3 Lbs. (1.4 Kg)

## Camera Specifications

Imager:	1/3" SONY EX-View HAD-II CCD
Iris:	Electronic
Lens:	3.6mm fixed lens
Minimum Illumination:	0.75 Lux (F1.2 normal shutter speed)
Resolution:	650 TVL
Scanning System:	2:1 interlaced
Signal System:	NTSC
Signal-to-Noise Ratio:	50 dB or greater
Synchronizing System:	Internal
Video:	BNC, 1Vp-p 75 ohm composite
White Balance:	1,800 - 10,500°K Auto tracking

## Electrical Specifications

Input Voltage:	15 - 28 Vac/Vdc
Power Consumption:	5va (watts)

## Mechanical Specifications

Construction Body:	16-gauge steel backbox
Face Plate:	12-gauge steel, powdercoated in off-white or stainless steel
Viewing Window:	1/8" polycarbonate with scratch resistant coating and Window Guard; paint shield
Operating Temperature:	0°F to 122°F (-18°C to 50°C)

## Shipping Specifications

Shipping Dimensions:	9" x 8" x 9" (228 x 203 x 229mm)
Shipping Weight:	4 Lbs. (1.9 Kg)

## A&E Specifications

The Warrior 6 camera shall include a 16-gauge steel back box with 3/4" conduit knockouts. The front cover shall be 12-gauge steel, powdercoated in off-white. There is an optional stainless steel front plate. The viewing window shall be constructed of 1/8" polycarbonate and shall include a scratch resistant coating and paint shield for high vandalism installations. A metal camera mounting bracket shall be included, allowing from 10° to 50° viewing angle. Available with a high resolution Day and Night fixed lens camera.

## Regulatory and Certifications



RoHS



WEEE

# MOOG

Sensor and Surveillance Systems

3650 Woodhead Drive Northbrook, IL, USA 60062

+1.847.498.0700 Fax: +1.847.498.1258 www.moogS3.com