Audiovideosupply VTC-TTAT2HR2F

2.1 Megapixel Outdoor HD-TVI/AHD/CVBS Turret Camera with 2 High Power IR LED Illumination





Also Available in Charcoal Gray (VTC-TTAT2HR2FB)

WEATHER RESISTANCE



TRANSCENDENT

FEATURES:

- 1/3" 2.1 MegaPixel CMOS Sensor
- HD-TVI & AHD/CVBS Video Output
- 3.6mm Fixed Iris Lens Included
- 2 High Power Infrared LED's with 65' IR Range
- Digital Wide Dynamic Range (D-WDR)
- True Mechanical Day/Night function by ICR
- 3D-DNR Noise Reduction
- IP66 Weather Resistance
- Supports Up The COAX Control
- Over 1500' HD Video Transmission (Depending on cable characteristics and integrity)
- Optional Junction Box Mount Available (VT-TJB01)
- Available in Ivory or Charcoal Gray
- 12VDC Operation

Transcendent Series High Definition 1080P HD-TVI, AHD, CVBS Cameras offer unprecedented performance and value.

FIXED

, cort

These simple, easy to install, attractively styled, analog HD Cameras transmit over your existing Coaxial cable at distances up to 1500'.

Use with VITEK Transcendent Series HD-TVI/HD-AHD/960H Recorders with IP Camera Support



Transcendent Series 4, 8 or 16 Channel Digital Video Recorder Supporting HD-TVI, AHD, and 960H Cameras as well as IP Cameras with Full 1080p Recording & Playback.



(888) VITEK-70 | WWW.VITEKCCTV.COM 28492 Constellation Road Valencia, CA 91355



www.avsupply.com | email: sales@avsupply.com | Ph: 858.565.1101

AUDioVideoSupply VTC-TTAT2HR2F^{2.}

2.1 Megapixel Outdoor HD-TVI/AHD/CVBS Turret Camera with 2 High Power IR LED Illumination

Specifications	
Image Sensor	1/3" 2.1 MegaPixel CMOS Sensor
Resolution	HD-TVI & AHD: 1080p (2.1 MegaPixel) / CVBS: 960H
Effective Pixels	1920(H) x 1080(V)
Signal System	PAL/NTSC
Video Output	1x HD-TVI (BNC) & 1 AHD/CVBS (BNC)
Lens	3.6mm Fixed
Day/Night	True Day/Night by ICR
S/N Ratio	>52dB (AGC OFF)
Auto Gain Control	0FF ~ 44.8dB
Min Illumination	O Lux (LED ON)
IR LEDs	2 x High Power
IR Distance	65'
Color-B/W Auto Switch	Yes
Electronic Shutter	1/50s~ 1/67500s
White Balance	AWB
WB Range	2300 ~ 9600K
BLC	Yes
WDR	Digtial WDR
Transmission Distance	Up to 1500' (Depending on cable characteristics & integrity)
Up the COAX Control	YES
Noise Reduction	Yes
Weather Resistance	IP66
Power Consumption	210mA (IR Off) / 375mA (IR On)
Power Supply	12VDC
Working Environment	-4~122 / 10%~90% Humidity
Weight	13.05 oz. / 0.82 lbs. / 370g
Dimensions	3.43" x 4.25" (87 × 108mm) Dia x H





VT-TJB01 Optional Junction Box for Cable Management for use with all Transcendent Bullet and Turret Style Cameras



(888) VITEK-70 | WWW.VITEKCCTV.COM 28492 Constellation Road Valencia, CA 91355



www.avsupply.com | email: sales@avsupply.com | Ph: 858.565.1101