

Professional LED Series

MONITORS
Professional LED Monitors

63



HDMI™
HIGH-DEFINITION MULTIMEDIA INTERFACE



VTM-LED221P & VTM-LED241P 22" / 24" Professional LED Monitor

- 22" / 24" Wide Screen LED Display Panel
- Professional grade display designed for 24/7 continuous use in security applications
- Dual HDMI, VGA, and BNC Composite Video Inputs with PC and Stereo Audio Inputs
- Resolution up to 1920 x 1080 (1080P)
- Contrast Ratio of 10,000:1
- Ultra High Dynamic Contrast provides more accurate colors
- 3D comb filter ensures clear contour lines of the image
- <5ms Response time
- 170° Horizontal Viewing Angle
- Picture In Picture (PIP) / POP (Picture On Picture) Display Options
- Top Panel Controls with included IR Remote Control
- VESA 100mm Standard Mounting
- 50,000 Hour Panel Life



IR Remote Control Included

Specifications	VTM-LED221P	VTM-LED241P
Screen Size	21.5"	23.6"
Display Type	LED	
Aspect Ratio	16:9	
Resolution	1080P (1920x1080)	
Response Time	<5ms	
Contrast Ratio	10,000:1	
Display Color	16.7 Million	
Brightness	300cd/m ²	
Pixel Type	Active Matrix TFT	
Pixel Pitch	0.24825 x 0.24825 mm	0.2715 x 0.2715 mm
Viewing Angle (H/V)	170° / 160°	170° / 160°
Video System	NTSC/PAL	
Video In/Out	1 BNC Input / 1 BNC Output (Looping)	
VGA In	1 (15Pin D-Sub)	
HDMI In	2	
Audio Input	Stereo RCA & 1/8" PC	
Built In speaker	Yes (1.5W x 2)	
PIP / POP	Analog / Digital	
Remote	YES	
3D Comb Filter	YES	
3D De-Interlace	YES	
Noise Reduction	YES	
Multi-Language	English, Spanish, German, French, Italian, Russian, Turkish, Japanese, Polish	
Stand Tilt	0° ~ 15°	
Vesa Mount Size	100mm x 100mm	
Power Adapter	12VDC (AC100/240 [50/60])	
Power Consumption	30W Max	35W Max
Certifications	UL, FCC-D0C, CE, ROHS	
Operating Temperature	32° to 104° F (0° to 40° C)	
Operating Humidity	10% to 90% relative, non-condensing	
Dimensions (w/Stand)	20.63" x 14.76" x 6.7"	22.83" x 16.02" x 6.7"
Weight	7.93 lbs (3.6Kgs)	9.7 lbs (4.4Kgs)

Rear Inputs

