

Macro lens for line scan

| Model | | VS-L1020-35/F | |
|---------------------------------|--------------------------|-------------------------|-------------------|
| Optical mag. range | | 1.0x~2.0x | |
| Optical mag. | | 1.0x | 2.0x |
| FOV | 5000bitx7u(35mm)Line | 35mm | 17.5mm |
| | 2048bitx10u(20.48mm)Line | 20.48mm | 10.24mm |
| | 2048bitx14u(28.6mm)Line | 28.6mm | 14.3mm |
| | 4096bitx7u(28.6mm)Line | 28.6mm | 14.3mm |
| WD | | 107.1mm | 76.1mm |
| O/I (Object & Imager distance) | | 242.8mm | 273.9mm |
| Focal Length (f) | | 62.06mm | |
| Working F/# *Value at Iris open | | 6.46 | 9.69 |
| NA *Value at Iris open | | 0.077 | 0.1 |
| Resolution *at λ 550nm | | 4.3u | 3.3u |
| DOF | at PCoC ϕ 0.04mm | 0.51mm | 0.19mm |
| | at PCoC ϕ 0.01mm | 0.13mm | 0.05mm |
| TV distortion (max.) | | 0.001 | |
| Wavelength | | Visible (400mm ~ 700nm) | |
| Camera mount | | F-mount | |
| Flange back | | 46.5mm | |
| Sensor size (max.) | | ϕ 35mm | |
| Co-axial prism | | - | |
| Weight (approx.) | | 356g | |
| Dimension | | ϕ_{54} | L= 89.2 ~ 151.2mm |

VS Technology Corporation