

Megapixel Full HD Armordome Camera

WDD-4399HD



- 2Megapixel full HD IP dome camera
- Up to 30fps@1080p (H.264)
- Progressive scan
- Dual streaming (H.264 & MJPEG)
- Power over ethernet
- Ultra compact design / rugged weatherproof housing
- Built-In Micro SDHC slot for storing snapshots & video clips
- Infra-red LED day & night - (WDD-4399HDN only)

SPECIFICATION

Camera	Image sensor		SONY IMX 122 1/3" 2.1Megapixel CMOS
	Scanning system		Progressive scan
	Lens		3.6mm fixed lens
	Electronic shutter speed		Auto / Flx;NTSC: 1/30 ~ 1/50,000sec PAL: 1/25 ~ 1/50,000sec
	White balance		AWB / manual / indoor / outdoor
	Backlight compensation		BLC / HLC / Off
	ACCE		Low / Middle / High / Off
	AGC		Low / Middle / High
	Day & night		Auto / BW / color / EXT (selectable)
	2D/3D-NR		2DNR / 3DNR / smart NR
	S/N Ratio		More than 50dB
	Min. Illumination		1.0 Lux (color), 0.5 Lux (BW), 0.02 (Sens-up x60)
WDR		-	
Intelligent video		-	
Video	Compression		H.264 @HP,MJPEG
	Streaming	H.264	UDP, TCP, HTTP or HTTPS
		MJPEG	HTTP or HTTPS
	Resolution	H.264	Up to 1080p
		MJPEG	352 x 192, 640 x 480, 1280 x 720
	Frame rate	H.264	Up to 30fps@1080p
MJPEG		Up to 30fps@720p	
Output		NTSC / PAL 1Vp-p 750hm composite	
Audio	Input / compression		Internal C-MIC (-30dB) / G.711 / AAC
	Output		Supports volume control & mute
Networking	Interface		10 / 100 Mbps ethernet, RJ-45
	ONVIF		Supported
	Protocols		IPv4, IPv6 (coming Soon), TCP / IP, HTTP, HTTPS, UPnP, RTP / RTSP, SMTP, FTP, DHCP, NTP, DNS, DDNS, QoS (Coming Soon), SNMP
Users		8 client monitoring at the same time	
Storage	File format		MP4
	SDHC		Buit-In micro-SDHC slot [4GB ~ 32GB] stores snapshots & video clips
Alarm & events	Motion detection		On / off (12zone selectable)
	Sensor & trigger out		1ch NO / NC input & 1ch NO / NC output
	Notifications		Event notification using SMTP, FTP
Applications Security	Security		Multi-level user access with password protection
	Security		IP address filtering / HTTPS encrypted data transmission
Connectors	Connectors		Ethernet: RJ-45; video output: 1x BNC jack; audio output:1x stereo phone jack; Alarm in / out: 4P strip wire; power input: 1x DC jack
	Power over ethernet		IEEE 802.3af, 13Watt
Power	Power supply / consump.		9 ~ 28VDC
	Maintenance Approvals		Firware upgrade: 16ch remote management (RMS)
Approvals		-	

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

weldex.com
oem@weldex.com
Tel: (714) 761-2100 [USA]
Fax:(714) 761-3811 [USA]
Tel:+49 (0)2102 528 2803 [GER]
Fax:+49 (0)2102 528 2804 [GER]

© 2014 Weldex
6751 Katella Avenue, Cypress, CA 90630 [USA]
Broichhof Strasse 5 D-40880 Ratingen, Germany [GER]



For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101

1-800-284-2288 sales@avsupply.com
www.avsupply.com


Megapixel Full HD Armordome Camera

SPECIFICATION

WDD-4399HD

Environmental	Operating temp. / hum.	-10°C ~ +60°C / 10 ~90 RH, non condensing
System	Operating system	Embedded linux
	Dimensions	4.17" x 3.0"
	Weight	-

DIMENSIONS (Unit: mm)



Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

weldex.com
oem@weldex.com
Tel: (714) 761-2100 [USA]
Fax: (714) 761-3811 [USA]
Tel: +49 (0)2102 528 2803 [GER]
Fax: +49 (0)2102 528 2804 [GER]

© 2014 Weldex
6751 Katella Avenue, Cypress, CA 90630 [USA]
Broichhof Strasse 5 D-40880 Ratingen, Germany [GER]

WELDEX

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101